

## SAFETY DATA SHEET

SEAL AND SPRAY

Page: 1

Compilation date: 14-12-2016

Revision No: 1

### Section 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

**Product name:** SEAL AND SPRAY

**Product code:** 5420-5421-5422

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Use of substance / mixture:** PROC7: Industrial spraying PROC11: Non industrial spraying

#### 1.3. Details of the supplier of the safety data sheet

**Company name:** ProPart International B.V.

Molenakker 3

Reuver

5953 TW

The Netherlands

**Tel:** +31 (0) 77 476 2368

**Fax:** +31 (0) 77 476 2424

**Email:** [info@propart-international.com](mailto:info@propart-international.com)

#### 1.4. Emergency telephone number

**Emergency tel:** +31 (0) 77 476 2368 (08.30-17.00)

### Section 2: Hazards identification

#### 2.1. Classification of the substance or mixture

**Classification under CLP:** Aquatic Chronic 3: H412; Flam. Aerosol 1: H222; Skin Sens. 1: H317; STOT SE 3: H336;  
Eye Irrit. 2: H319; Skin Irrit. 2: H315; -: EUH066; -: H229

**Most important adverse effects:** Repeated exposure may cause skin dryness or cracking. Extremely flammable aerosol.  
Pressurised container: May burst if heated. May cause an allergic skin reaction. May cause drowsiness or dizziness. Harmful to aquatic life with long lasting effects.

#### 2.2. Label elements

**Label elements:**

**Hazard statements:** EUH066: Repeated exposure may cause skin dryness or cracking.

H222: Extremely flammable aerosol.

H229: Pressurised container: May burst if heated

H317: May cause an allergic skin reaction.

H336: May cause drowsiness or dizziness.

H412: Harmful to aquatic life with long lasting effects.

**Hazard pictograms:** GHS02: Flame

GHS07: Exclamation mark

# SAFETY DATA SHEET

SEAL AND SPRAY

Page: 2



**Signal words:** Danger

**Precautionary statements:** P501: Dispose of contents/container to an approved waste disposal according to local/regional/national/international regulations.

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211: Do not spray on an open flame or other ignition source.

P251: Do not pierce or burn, even after use.

P410+412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

P260: Do not breathe spray.

P102: Keep out of reach of children.

## 2.3. Other hazards

**PBT:** This product is not identified as a PBT/vPvB substance.

## Section 3: Composition/information on ingredients

### 3.2. Mixtures

#### Hazardous ingredients:

##### N-BUTYL ACETATE

EINECS	CAS	PBT / WEL	CLP Classification	Percent
204-658-1	123-86-4	-	Flam. Liq. 3: H226; STOT SE 3: H336; -: EUH066	10-30%

##### PROPANE - REACH registered number(s): 01-2119486944-21-XXXX

200-827-9	74-98-6	Substance with a Community workplace exposure limit.	Flam. Gas 1: H220; Press. Gas: H280	10-30%
-----------	---------	--	-------------------------------------	--------

##### ETHYL ACETATE

205-500-4	141-78-6	-	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336; -: EUH066	1-10%
-----------	----------	---	--	-------

##### HYDROCARBONS, C7-C9, N-ALKANES, ISOALKANES, CYCLICS - REACH registered number(s): 01-2119475515-33

-	-	-	STOT SE 3: H335; STOT SE 3: H336; Flam. Liq. 2: H225; Asp. Tox. 1: H304; Skin Irrit. 2: H315; Aquatic Chronic 2: H411	1-10%
---	---	---	---	-------

[cont...]

# SAFETY DATA SHEET

## SEAL AND SPRAY

Page: 3

BUTANE - REACH registered number(s): 01-2119474691-32-XXXX

203-448-7	106-97-8	Substance with a Community workplace exposure limit.	Flam. Gas 1: H220; Press. Gas: H280	1-10%
-----------	----------	--	-------------------------------------	-------

ISOBUTANE

200-857-2	75-28-5	Substance with a Community workplace exposure limit.	Flam. Gas 1: H220; Press. Gas: H280	1-10%
-----------	---------	--	-------------------------------------	-------

ROSIN

232-475-7	8050-09-7	-	Skin Sens. 1: H317	1-10%
-----------	-----------	---	--------------------	-------

XYLENE

215-535-7	1330-20-7	-	Flam. Liq. 3: H226; Acute Tox. 4: H332; Acute Tox. 4: H312; Skin Irrit. 2: H315	1-10%
-----------	-----------	---	---	-------

VINYLTRIMETHOXYSILANE

220-449-8	2768-02-7	-	Flam. Liq. 2: H225; Skin Irrit. 2: H315; Eye Irrit. 2: H319	1-10%
-----------	-----------	---	---	-------

(3-AMINOPROPYL)TRIMETHOXYSILANE

237-511-5	13822-56-5	-	Skin Irrit. 2: H315; Eye Dam. 1: H318	1-10%
-----------	------------	---	---------------------------------------	-------

## Section 4: First aid measures

### 4.1. Description of first aid measures

**Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water. Consult a doctor.

**Eye contact:** Bathe the eye with running water for 15 minutes. Consult a doctor.

**Ingestion:** Wash out mouth with water. Consult a doctor.

**Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

### 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and redness. The eyes may water profusely.

**Ingestion:** There may be soreness and redness of the mouth and throat.

**Inhalation:** Exposure may cause coughing or wheezing.

**Delayed / immediate effects:** Delayed effects can be expected after long-term exposure.

### 4.3. Indication of any immediate medical attention and special treatment needed

**Immediate / special treatment:** Not applicable.

## Section 5: Fire-fighting measures

### 5.1. Extinguishing media

**Extinguishing media:** Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

[cont...]

# SAFETY DATA SHEET

SEAL AND SPRAY

Page: 4

## 5.2. Special hazards arising from the substance or mixture

**Exposure hazards:** In combustion emits toxic fumes.

## 5.3. Advice for fire-fighters

**Advice for fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

## Section 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions:** Do not attempt to take action without suitable protective clothing - see section 8 of SDS.  
Turn leaking containers leak-side up to prevent the escape of liquid.

### 6.2. Environmental precautions

**Environmental precautions:** Do not discharge into drains or rivers. Contain the spillage using bunding.

### 6.3. Methods and material for containment and cleaning up

**Clean-up procedures:** Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

### 6.4. Reference to other sections

**Reference to other sections:** Refer to section 8 of SDS.

## Section 7: Handling and storage

### 7.1. Precautions for safe handling

**Handling requirements:** Avoid direct contact with the substance. Avoid the formation or spread of mists in the air.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage conditions:** Store in a cool, well ventilated area. Keep container tightly closed.

### 7.3. Specific end use(s)

**Specific end use(s):** No data available.

## Section 8: Exposure controls/personal protection

### 8.1. Control parameters

**Hazardous ingredients:**

**N-BUTYL ACETATE**

**Workplace exposure limits:**

**Respirable dust**

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	724 mg/m <sup>3</sup>	966 mg/m <sup>3</sup>	-	-

[cont...]

# SAFETY DATA SHEET

SEAL AND SPRAY

Page: 5

## PROPANE

UK	1800 mg/m <sup>3</sup>	7200 mg/m <sup>3</sup>	-	-
----	------------------------	------------------------	---	---

## ETHYL ACETATE

UK	200 ppm	400 ppm	-	-
----	---------	---------	---	---

## BUTANE

UK	1450 mg/m <sup>3</sup>	1810 mg/m <sup>3</sup>	-	-
----	------------------------	------------------------	---	---

## ISOBUTANE

UK	2400 mg/m <sup>3</sup>	9600 mg/m <sup>3</sup>	-	-
----	------------------------	------------------------	---	---

## ROSIN

UK	0.05 mg/m <sup>3</sup>	0.15 mg/m <sup>3</sup>	-	-
----	------------------------	------------------------	---	---

## XYLENE

UK	220 mg/m <sup>3</sup>	441 mg/m <sup>3</sup>	-	-
----	-----------------------	-----------------------	---	---

## DNEL/PNEC Values

**DNEL / PNEC** No data available.

## 8.2. Exposure controls

**Engineering measures:** Ensure there is sufficient ventilation of the area.

**Respiratory protection:** Self-contained breathing apparatus must be available in case of emergency.

**Hand protection:** Impermeable gloves.

**Eye protection:** Safety glasses. Ensure eye bath is to hand.

**Skin protection:** Impermeable protective clothing.

## Section 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

**State:** Aerosol

**Colour:** Black

**Odour:** Characteristic odour

**Evaporation rate:** Not applicable.

**Solubility in water:** Not miscible

**Boiling point/range°C:** Not applicable.

**Melting point/range°C:** No data available.

**Flammability limits %: lower:** 1.2

**upper:** 10.9

**Flash point°C:** <0°C

**Part.coeff. n-octanol/water:** No data available.

**Autoflammability°C:** Not applicable.

**Vapour pressure:** 3500hPa

**pH:** No data available.

**VOC g/l:** 539.0

### 9.2. Other information

**Other information:** Density at 20°C (68°F): 0.879 g/cm<sup>3</sup> (7.335 lbs/gal)

[cont...]

# SAFETY DATA SHEET

SEAL AND SPRAY

Page: 6

## Section 10: Stability and reactivity

### 10.1. Reactivity

**Reactivity:** Stable under recommended transport or storage conditions.

### 10.2. Chemical stability

**Chemical stability:** Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

**Hazardous reactions:** Hazardous reactions will not occur under normal transport or storage conditions.  
Decomposition may occur on exposure to conditions or materials listed below.

### 10.4. Conditions to avoid

**Conditions to avoid:** Heat.

### 10.5. Incompatible materials

**Materials to avoid:** Strong oxidising agents. Strong acids.

### 10.6. Hazardous decomposition products

**Haz. decomp. products:** In combustion emits toxic fumes.

## Section 11: Toxicological information

### 11.1. Information on toxicological effects

#### Hazardous ingredients:

#### N-BUTYL ACETATE

ORL	MUS	LD50	6	gm/kg
ORL	RAT	LD50	10768	mg/kg

#### ETHYL ACETATE

ORL	MUS	LD50	4100	mg/kg
ORL	RAT	LD50	5620	mg/kg
SCU	RAT	LDLO	5	gm/kg

#### XYLENE

ORL	MUS	LD50	2119	mg/kg
ORL	RAT	LD50	4300	mg/kg
SCU	RAT	LD50	1700	mg/kg

#### Relevant hazards for product:

Hazard	Route	Basis
--------	-------	-------

[cont...]

# SAFETY DATA SHEET

SEAL AND SPRAY

Page: 7

Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated
Respiratory/skin sensitisation	DRM	Hazardous: calculated
STOT-single exposure	-	Hazardous: calculated

## Symptoms / routes of exposure

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and redness. The eyes may water profusely.

**Ingestion:** There may be soreness and redness of the mouth and throat.

**Inhalation:** Exposure may cause coughing or wheezing.

**Delayed / immediate effects:** Delayed effects can be expected after long-term exposure.

**Other information:** STOT-single exposure: May cause drowsiness or dizziness

## Section 12: Ecological information

### 12.1. Toxicity

#### Ecotoxicity values:

Species	Test	Value	Units
CAS 141-78-6	-	-	-
Pimephales promelas	96H LC50	18	mg/l
Daphnia magna	24H LC50	205	mg/l
ALGAE	96H EC50	320	mg/l
Daphnia magna	48H EC50	44	mg/l
Cas 123-86-4	-	-	-

### 12.2. Persistence and degradability

**Persistence and degradability:** Biodegradable.

### 12.3. Bioaccumulative potential

**Bioaccumulative potential:** No bioaccumulation potential.

### 12.4. Mobility in soil

**Mobility:** Readily absorbed into soil.

### 12.5. Results of PBT and vPvB assessment

**PBT identification:** This product is not identified as a PBT/vPvB substance.

### 12.6. Other adverse effects

**Other adverse effects:** Negligible ecotoxicity.

## Section 13: Disposal considerations

[cont...]

# SAFETY DATA SHEET

SEAL AND SPRAY

Page: 8

## 13.1. Waste treatment methods

**Disposal operations:** Transfer to a suitable container and arrange for collection by specialised disposal company.

**Disposal of packaging:** Non contaminated packagings may be recycled

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

## Section 14: Transport information

### 14.1. UN number

**UN number:** UN1950

### 14.2. UN proper shipping name

**Shipping name:** AEROSOLS

### 14.3. Transport hazard class(es)

**Transport class:** 2

### 14.4. Packing group

### 14.5. Environmental hazards

**Environmentally hazardous:** No

**Marine pollutant:** No

### 14.6. Special precautions for user

**Special precautions:** No special precautions.

**Tunnel code:** D

**Transport category:** 2

## Section 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

**Specific regulations:** Directive 2012/18/EU

### 15.2. Chemical Safety Assessment

**Chemical safety assessment:** A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

## Section 16: Other information

### Other information

**Other information:** This safety data sheet is prepared in accordance with Commission Regulation (EU) No 2015/830.

\* indicates text in the SDS which has changed since the last revision.

**Phrases used in s.2 and s.3:** EUH066: Repeated exposure may cause skin dryness or cracking.

H220: Extremely flammable gas.

H222: Extremely flammable aerosol.

[cont...]



## SAFETY DATA SHEET

### SEAL AND SPRAY

Page: 9

- H225: Highly flammable liquid and vapour.
- H226: Flammable liquid and vapour.
- H229: Pressurised container: May burst if heated
- H304: May be fatal if swallowed and enters airways.
- H312: Harmful in contact with skin.
- H315: Causes skin irritation.
- H317: May cause an allergic skin reaction.
- H318: Causes serious eye damage.
- H319: Causes serious eye irritation.
- H332: Harmful if inhaled.
- H335: May cause respiratory irritation.
- H336: May cause drowsiness or dizziness.
- H411: Toxic to aquatic life with long lasting effects.
- H412: Harmful to aquatic life with long lasting effects.

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.