

# TOP GLIDE

Tire mounting spray

- ✓ **Easy in use**
- ✓ **Evaporates without leaving any residue**
- ✓ **Very versatile**
- ✓ **Does not leave greasy smears**

## PRODUCT DESCRIPTION:

**TOP GLIDE** can be used for mounting and dismounting rubber parts, reducing frictional resistance. Facilitates assembly and disassembly in a simple way. Top glide evaporates quickly and evaporates without leaving a residue. No dirty smears remain on the surface.

## APPLICATIONS:

Mounting tires on rims, especially for:

- Low profile, flat tires.
- For pulling cables through pipes and conduits.
- Mounting of hoses, rubber plugs, door seals, rubber covers, silent blocks, etc.

## INSTRUCTIONS:

Before use, read and follow the instructions on the label. Bring the aerosol to room temperature. The ideal processing temperature is 5°C to 30°C. Shake the aerosol before use. Apply the Top Glide in a thin layer. The best lubrication is obtained after evaporation of the solvent.

## SPECIFICATIONS:

Base	Volatile silicone oils, water, emulsifiers, preservatives, anti-corrosion additives
Propellant	Propane/Butane
Appearance	Oil/Fat
Pressure (20°C)	4 bar
Spray pattern	Mist, white greasy emulsion
Non-Volatile General Aerosol	About 1%
Spray rate (20°C)	About 25 - 30 tires can be treated with 1 aerosol. (16 - 14 inches).
Density (20°C)	Ca. 0,88 g/ml

<b>Article number:</b>	<b>Color:</b>
1220	Transparent

