

SEAL & SPRAY - BLACK (500 ML)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830
Issue date: 8/23/2021 Revision date: 4/13/2021 Supersedes version of: 11/6/2019 Version: 9.1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Trade name : SEAL & SPRAY - BLACK (500 ML)
UFI : YW2G-105H-1003-TAAS
Product code : 5450

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Professional use
Use of the substance/mixture : Preparation

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Pro Part International
Molenakker 3
5953 TW Reuver - Nederland
T +31 (0) 77 476 2204
info@propart-international.com - www.propart-international.com

1.4. Emergency telephone number

No additional information available

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP] Mixtures/Substances: SDS EU > 2015: According to Regulation (EU) 2015/830, 2020/878 (REACH Annex II)

Aerosol, Category 1	H222;H229
Skin corrosion/irritation, Category 2	H315
Serious eye damage/eye irritation, Category 2	H319
Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation	H335
Specific target organ toxicity — Repeated exposure, Category 2	H373
Full text of H-statements: see section 16	

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



Signal word (CLP) : Danger
Contains : XYLENE
Hazard statements (CLP) : H222 - Extremely flammable aerosol.
H229 - Pressurised container: May burst if heated.
H315 - Causes skin irritation.

SEAL & SPRAY - BLACK (500 ML)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Precautionary statements (CLP)	H319 - Causes serious eye irritation. H335 - May cause respiratory irritation. H373 - May cause damage to organs through prolonged or repeated exposure.
	: P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 - Do not spray on an open flame or other ignition source. P251 - Do not pierce or burn, even after use. P260 - Do not breathe spray. P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C. P501 - Dispose of Contents and container, to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.
EUH-statements	: EUH208 - Contains 2-BUTANONE OXIME . May produce an allergic reaction.

2.3. Other hazards

Component	
DIMETHYL ETHER (115-10-6)	The product does not meet the PBT and vPvB classification criteria

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605

SECTION 3: Composition/information on ingredients

3.1. Substances

No data available

3.2. Mixtures

Comments : Mixture of substances listed one after the other with non-hazardous additions

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
DIMETHYL ETHER substance with a Community workplace exposure limit	CAS-No.: 115-10-6 EC-No.: 204-065-8 EC Index-No.: 603-019-00-8 REACH-no: 01-2119472128-37	25 – 50	Flam. Gas 1A, H220 Press. Gas (Comp.), H280
XYLENE substance with a Community workplace exposure limit	EC-No.: 905-588-0 REACH-no: 01-2119488216-32	25 – 50	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304
ETHYLBENZENE substance with a Community workplace exposure limit	CAS-No.: 100-41-4 EC-No.: 202-849-4 EC Index-No.: 601-023-00-4 REACH-no: 01-2119489370-35	2.5 – 5	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation), H332 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Chronic 3, H412

SEAL & SPRAY - BLACK (500 ML)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
2-BUTANONE OXIME	CAS-No.: 96-29-7 EC-No.: 202-496-6 EC Index-No.: 616-014-00-0 REACH-no: 01-2119539477-28	< 1	Carc. 2, H351 Acute Tox. 4 (Dermal), H312 Eye Dam. 1, H318 Skin Sens. 1, H317

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Symptoms of poisoning may not appear for several hours. Keep under medical supervision for at least 48 hours.
First-aid measures after inhalation	: With unconsciousness; location and transport in a stable side position.
First-aid measures after skin contact	: Wash immediately with plenty of soap and water. Rinse well.
First-aid measures after eye contact	: Immediately rinse with water for a prolonged period while holding the eyelids wide open. If eye irritation persists and/or symptoms, obtain medical attention.
First-aid measures after ingestion	: Drink plenty of water. Move to fresh air. Get immediate medical advice/attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: No additional data.
------------------	-----------------------

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Coordinate fire-fighting equipment to the environment.
------------------------------	--

5.2. Special hazards arising from the substance or mixture

Reactivity in case of fire	: Toxic gases are formed when heated or burned.
----------------------------	---

5.3. Advice for firefighters

Protection during firefighting	: Wear suitable protective clothing. Approved respirator.
--------------------------------	---

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Wear suitable respiratory protection. Use protective clothing. Keep unprotected people away. Provide adequate ventilation. Keep away from ignition sources.
------------------	---

6.1.1. For non-emergency personnel

No additional information available

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Do not allow to enter sewers, surface or groundwater.

SEAL & SPRAY - BLACK (500 ML)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

6.3. Methods and material for containment and cleaning up

- Methods for cleaning up : For disposal of contaminated materials refer to section 13 : "Disposal considerations".
Ensure adequate air ventilation.
- Other information : Ensure adequate air ventilation.

6.4. Reference to other sections

Information regarding safe use, see chapter 7. Wear personal protective clothing (see chapter 8). Information regarding storage, see chapter 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Additional hazards when processed : Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Have respirators ready.
- Precautions for safe handling : Ensure good extraction / ventilation of the workplace.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : The government provisions with regard to the storage of compressed gas packings must be observed. Keep tanks tightly closed.
- Information on mixed storage : Not necessary under the recommended storage and handling conditions.
- Storage area : Category 2B.

7.3. Specific end use(s)

No additional information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. National occupational exposure and biological limit values

SEAL & SPRAY - BLACK (500 ML)	
EU - Indicative Occupational Exposure Limit (IOEL)	
	The basis of the information is the data that were valid when compiled.
DIMETHYL ETHER (115-10-6)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Dimethylether
IOEL TWA	950 mg/m ³
IOEL TWA [ppm]	495 ppm
IOEL STEL	1500 mg/m ³
IOEL STEL [ppm]	782 ppm
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
Netherlands - Occupational Exposure Limits	
Local name	Dimethylether
MAC-TGG (OEL TWA)	950 mg/m ³
MAC-15 (OEL STEL)	1500 mg/m ³
Regulatory reference	Arbeidsomstandighedenregeling 2021

SEAL & SPRAY - BLACK (500 ML)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

ETHYLBENZENE (100-41-4)	
EU - Indicative Occupational Exposure Limit (IOEL)	
IOEL TWA	215 mg/m ³
IOEL TWA [ppm]	49 ppm
IOEL STEL	430 mg/m ³
IOEL STEL [ppm]	98 ppm
XYLENE	
EU - Indicative Occupational Exposure Limit (IOEL)	
IOEL TWA	210 mg/m ³
IOEL TWA [ppm]	47 ppm
IOEL STEL	442 mg/m ³
IOEL STEL [ppm]	100 ppm
Netherlands - Occupational Exposure Limits	
MAC-TGG (OEL TWA)	221 mg/m ³
MAC-TGG (OEL TWA) [ppm]	50 ppm
MAC-15 (OEL STEL)	442 mg/m ³
MAC-15 (OEL STEL) [ppm]	100 ppm

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

Additional information

: The basis of the information is the data that were valid when compiled.

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

No additional data, see chapter 7.

8.2.2. Personal protection equipment

Personal protective equipment:

Gas mask. Gloves. Protective goggles.

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:

Safety glasses

8.2.2.2. Skin protection

Skin and body protection:

Wash clothing before re-using. Completely skin-covering anti-static, chemical and oil resistant clothing

SEAL & SPRAY - BLACK (500 ML)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Hand protection:

Choosing the proper glove is a decision that depends not only on the type of material, but also on other quality features, which differ for each manufacturer. Butyl rubber gloves with a thickness of 0.4 mm are resistant to: Acetone : 480 min, Butyl acetates : 60 min, Ethyl acetate : 170 min, Xylenes : 42 min. Butyl rubber gloves with a thickness of 0.4 mm are solvent resistant for 42 - 480 minutes. For safety reasons, we advise users and persons responsible for safety at work to assume a solvent resistance of 42 minutes. In view of the information in section 3 of this SDS, a longer resistance duration can be assumed in certain cases. As the product is a mixture of several substances, the resistance of the glove material can not be predicted in advance with total reliability and has therefore to be checked prior to the application.

8.2.2.3. Respiratory protection

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device. Filter A2/P3

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Other information:

Remove/Take off immediately all contaminated clothing. Wash hands before breaks and after work. Keep away from food, drink and animal feedingstuffs. Store protective clothing separately. Do not breathe gas/vapour/aerosol. Avoid contact with skin and eyes.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Gas
Colour	: Black.
Appearance	: aerosol.
Odour	: Solvent.
Odour threshold	: Not determined.
Melting point	: Not determined.
Freezing point	: Not determined.
Boiling point	: Not usable due to aerosol
Flammability	: Not applicable
Explosive properties	: Not determined.
Explosive limits	: Not available
Lower explosive limit (LEL)	: 1 vol %
Upper explosive limit (UEL)	: 26.2 vol %
Flash point	: Not usable due to aerosol
Auto-ignition temperature	: 240 °C
Decomposition temperature	: Not determined.
pH	: Not determined.
Viscosity, kinematic	: Not determined.
Viscosity, dynamic	: Not determined.
Solubility	: Water: Not miscible/Practically not miscible Organic solvent:59,7 %
Partition coefficient n-octanol/water (Log Kow)	: Not available
Partition coefficient n-octanol/water (Log Pow)	: Not determined.
Vapour pressure	: 4000 hPa @ 20°C
Vapour pressure at 50 °C	: Not available
Density	: 1 g/cm ³ @ 20 °C
Relative density	: Not determined.
Relative vapour density at 20 °C	: Not determined.
Particle size	: No data available
Particle size distribution	: 30.8 % Solids content
Particle shape	: No data available
Particle aspect ratio	: No data available
Particle aggregation state	: No data available
Particle agglomeration state	: No data available
Particle specific surface area	: No data available
Particle dustiness	: No data available

SEAL & SPRAY - BLACK (500 ML)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

VOC content : 577.9 g/l VOC-EU: 59,70%

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available.

10.2. Chemical stability

No degradation when used as directed.

10.3. Possibility of hazardous reactions

No dangerous reactions known.

10.4. Conditions to avoid

Do not spray on an open flame or other ignition source. Keep away from ignition sources. When using do not smoke.

10.5. Incompatible materials

No additional information available.

10.6. Hazardous decomposition products

No hazardous decomposition products known.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Based on available data, the classification criteria are not met
Acute toxicity (dermal) : Based on available data, the classification criteria are not met
Acute toxicity (inhalation) : Based on available data, the classification criteria are not met

ETHYLBENZENE (100-41-4)	
LD50 oral rat	3500 mg/kg
XYLENE	
LD50 oral rat	3523 mg/kg
LD50 dermal	2000 mg/kg rabbit
LC50 Inhalation - Rat	29000 mg/m ³ (4 h)

Skin corrosion/irritation : Causes skin irritation.
pH: Not determined.

Serious eye damage/irritation : Causes serious eye irritation.
pH: Not determined.

Respiratory or skin sensitisation : Based on available data, the classification criteria are not met

Germ cell mutagenicity : Based on available data, the classification criteria are not met

Carcinogenicity : Based on available data, the classification criteria are not met

Reproductive toxicity : Based on available data, the classification criteria are not met

STOT-single exposure : May cause respiratory irritation.

STOT-repeated exposure : May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard : Based on available data, the classification criteria are not met

SEAL & SPRAY - BLACK (500 ML)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SEAL & SPRAY - BLACK (500 ML)

Viscosity, kinematic	Not determined.
----------------------	-----------------

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute) : Not classified

Hazardous to the aquatic environment, long-term (chronic) : Not classified

DIMETHYL ETHER (115-10-6)

LC50 - Other aquatic organisms [1]	> 4000 mg/l Daphnia magna (Water flea) 48h
------------------------------------	--

LC50 - Other aquatic organisms [2]	> 4000 mg/l Fish (96h)
------------------------------------	------------------------

EC50 96h - Algae [2]	155 mg/l algae
----------------------	----------------

XYLENE

LC50 - Fish [2]	13.5 mg/l
-----------------	-----------

EC50 - Crustacea [2]	7.4 mg/l
----------------------	----------

12.2. Persistence and degradability

SEAL & SPRAY - BLACK (500 ML)

Persistence and degradability	No additional information available.
-------------------------------	--------------------------------------

12.3. Bioaccumulative potential

SEAL & SPRAY - BLACK (500 ML)

Partition coefficient n-octanol/water (Log Pow)	Not determined.
---	-----------------

Bioaccumulative potential	No additional information available.
---------------------------	--------------------------------------

DIMETHYL ETHER (115-10-6)

Partition coefficient n-octanol/water (Log Pow)	-0.18
---	-------

12.4. Mobility in soil

SEAL & SPRAY - BLACK (500 ML)

Mobility in soil	No supplementary information available
------------------	--

Water hazard (NL)	Z (1) Non-degradable substances with hazardous properties for humans and the environment (carcinogenicity / mutagenicity / reprotoxicity / bioacumulative potential / toxicity or persistence
-------------------	---

Additional information	Hazardous to water (WGK 2(D)Self classification). Do not discharge undiluted or in large quantities into groundwater, surface water or sewage. Danger to drinking water even if small amounts leak into the ground.
------------------------	---

12.5. Results of PBT and vPvB assessment

SEAL & SPRAY - BLACK (500 ML)

Results of PBT assessment	The product does not meet the PBT and vPvB classification criteria
---------------------------	--

SEAL & SPRAY - BLACK (500 ML)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Component

DIMETHYL ETHER (115-10-6)

The product does not meet the PBT and vPvB classification criteria

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

Other adverse effects : No additional information available




SECTION 13: Disposal considerations

13.1. Waste treatment methods

Sewage disposal recommendations : Do not dispose of with domestic waste.
Product/Packaging disposal recommendations : Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.
European List of Waste (LoW) code : 08 01 11* - waste paint and varnish containing organic solvents or other dangerous substances
15 01 04 - metallic packaging

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA

ADR	IMDG	IATA
14.1. UN number or ID number		
UN 1950	UN 1950	UN 1950
14.2. UN proper shipping name		
AEROSOLS	AEROSOLS	Aerosols, flammable
Transport document description		
UN 1950 AEROSOLS, 2.1, (D)	UN 1950 AEROSOLS, 2.1	UN 1950 Aerosols, flammable, 2.1
14.3. Transport hazard class(es)		
2.1	2.1	2.1
		
14.4. Packing group		
No data available	No data available	No data available
14.5. Environmental hazards		
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No
Not applicable.		

14.6. Special precautions for user

Special transport precautions : Warning , Gases (except aerosol dispensers and lighters)

Overland transport

Classification code (ADR) : 5F
Limited quantities (ADR) : 1I

SEAL & SPRAY - BLACK (500 ML)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Excepted quantities (ADR) : E0
Transport category (ADR) : 2
Tunnel restriction code (ADR) : D

Transport by sea

Limited quantities (IMDG) : 1 L
Excepted quantities (IMDG) : E0
EmS-No. (Fire) : F-D
EmS-No. (Spillage) : S-U
Stowage and handling (IMDG) : SW1, SW22
Segregation (IMDG) : SG69

Air transport

No data available

14.7. Maritime transport in bulk according to IMO instruments

No data available

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

EU restriction list (REACH Annex XVII)		
Reference code	Applicable on	Entry title or description
3(a)	XYLENE ; ETHYLBENZENE	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F
3(b)	XYLENE ; ETHYLBENZENE ; 2- BUTANONE OXIME	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10
40.	DIMETHYL ETHER ; XYLENE ; ETHYLBENZENE	Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or not.

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

VOC content : 577.9 g/l VOC-EU: 59,70%

Directive 2012/18/EU (SEVESO III)

Seveso Additional information : P3a Flammable aerosol

15.1.2. National regulations

Qualifying quantity (tonnes) for application of requirements for high-threshold devices: 500 t

Qualifying quantity (tonnes) for applications of requirements for low-threshold devices: 150 t

Water Hazard Class: 2 (D) Hazardous to water in general

Germany

Water hazard class (WGK) : WGK: 3, Highly hazardous to water (Classification according to AwSV, Annex 1)

Hazardous Incident Ordinance (12. BImSchV) : Is not subject of the Hazardous Incident Ordinance (12. BImSchV)

Storage class (LGK, TRGS 510) : LGK 2B - Aerosol dispensers and lighters

SEAL & SPRAY - BLACK (500 ML)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Netherlands

SZW-lijst van kankerverwekkende stoffen : 2-BUTANONE OXIME is listed
SZW-lijst van mutagene stoffen : None of the components are listed
SZW-lijst van reprotoxische stoffen – Borstvoeding : None of the components are listed
SZW-lijst van reprotoxische stoffen – Vruchtbaarheid : None of the components are listed
SZW-lijst van reprotoxische stoffen – Ontwikkeling : None of the components are listed

Switzerland

Storage class (LK) : LK 2 - Liquefied or pressurized gases

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out

SECTION 16: Other information

Indication of changes:

This sheet has been revised completely (changes were not marked).

Indication of changes			
Section	Changed item	Change	Comments
	Respiratory or skin sensitisation - comment	Added	
	Particle size distribution	Modified	
1.2	Use of the substance/mixture	Modified	
2.2	EUH-statements	Added	
2.2	Precautionary statements (CLP)	Modified	
3	Composition/information on ingredients	Modified	
4.1	First-aid measures general	Modified	
4.1	First-aid measures after inhalation	Modified	
4.1	First-aid measures after eye contact	Modified	
6.1	General measures	Modified	
6.2	Environmental precautions	Modified	
7.1	Precautions for safe handling	Modified	
8.2	Skin and body protection	Modified	
8.2	Other information	Modified	
8.2	Personal protective equipment	Modified	
8.2	Eye protection	Modified	
9.1	Solubility in organic solvents	Added	
9.1	Relative vapour density at 20 °C	Added	
9.1	Upper explosive limit (UEL)	Modified	
9.1	Lower explosive limit (LEL)	Modified	
9.1	Auto-ignition temperature	Modified	
9.1	Vapour pressure	Modified	
9.1	Density	Modified	
9.2	VOC content	Modified	
10.4	Conditions to avoid	Modified	

SEAL & SPRAY - BLACK (500 ML)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Indication of changes			
Section	Changed item	Change	Comments
12.5	Results of PBT assessment	Added	
15.1	VOC content	Modified	

Abbreviations and acronyms	
CAS-No.	Chemical Abstract Service number
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
EC50	Median effective concentration
EC-No.	European Community number
EN	European Standard
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Dose leading to death in 50% of a test population (median lethal dose)
PBT	Persistent Bioaccumulative Toxic
vPvB	Very Persistent and Very Bioaccumulative
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
SDS	Safety Data Sheet
VOC	Volatile Organic Compounds
WGK:	Water Hazard Class

Data sources

: These data are based on the current state of our knowledge. However, they do not provide a guarantee of product properties and do not establish a contractual legal relationship.
Classification procedure: . Health and Environmental Hazards: The method for classifying mixtures based on the components of the mixture (sum formula). Physical and Chemical Properties: Classification is based on the results of the mixtures tested.

Full text of H- and EUH-statements	
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
Carc. 2	Carcinogenicity, Category 2
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Gas 1A	Flammable gases, Category 1A
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Press. Gas (Comp.)	Gases under pressure : Compressed gas

SEAL & SPRAY - BLACK (500 ML)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Full text of H- and EUH-statements	
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.
EUH208	Contains 2-BUTANONE OXIME . May produce an allergic reaction.

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.