

LIQUID GASKET

Engine & Fuel

- ✓ **Excellent resistance to fuels, oils and greases**
- ✓ **Resistance to high temperatures**
- ✓ **Very easy to apply**
- ✓ **Permanently elastic after hardening**

PRODUCT DESCRIPTION:

LIQUID GASKET is a temperature-resistant elastic seal, a silicone sealant that replaces all corks, felts, fibers, papers and rubber seals of all thicknesses and widths. The liquid seal is resistant to water, diluted inorganic solvents. In addition, the liquid seal is poorly resistant to aromatic solvents, acid concentrates and chlorinated hydrocarbons.

APPLICATIONS:

Liquid Gasket is ideal for sealing: machine and engine parts, threaded fittings, flange fittings, air ducts, compressors, pumps, turbines, transmissions, gasoline and water pumps, crankcase and valve covers, cooling systems, drainage systems, heat exchangers. Also suitable for the formation of seals and sealing rings.

SPECIFICATIONS:

Base	Polysiloxane
Curing system	Moisture cure
Skin formation time at 23°C and 50% RV	7 minutes
Cure time at at 23°C and 50% RV	2 mm / 24 hours
Shore A Hardness	30 +/- 5
Density	1,28 g/ml
Elastic recovery ISO 7389	>80%
Tensile strength	2,50 n/mm ²
Elasticity ISO 37	100% at 0,77 n/mm ²
Elongation at break test ISO 37	+/- 500%
Temperature resistance	-60°C up to + 285°C
Processing temperature	+5°C up to +35°C
Shelf life	In unopened original packaging, stored in a cool dry place between +5°C and +25°C, the product will last up to 15 months after the production date

Article number:	Color:	Quantity:
8000	Black	200 ml
8001	Black	310 ml

