

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 Issue date: 6/8/2020 Revision date: 6/8/2020 Supersedes: 2/7/2020 Version: 3.1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture

Trade name : Ultra Degreaser Spray (500ml)

Product code : 2001

Type of product : Cleaning product

Product group : Solvent cleaner, cold cleaner

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Industrial/Professional use spec : Professional

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Pro Part International Molenakker 3 5953 TW Reuver - Nederland T +31 (0) 77 476 2204

info@propart-international.com - www.propart-international.com

1.4. Emergency telephone number

No additional information available

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol, Category 1 H222;H229
Skin corrosion/irritation, Category 2 H315
Serious eye damage/eye irritation, Category 2 H319
Specific target organ toxicity — Single exposure, Category 3, Narcosis H336
Aspiration hazard, Category 1 H304
Hazardous to the aquatic environment — Chronic Hazard, Category 2 H411

Full text of H statements : see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Signal word (CLP)

Hazardous ingredients

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)





IS02 GHS07

: Danger

: HYDROCARBONS, C6-C7, N-ALKANES, ISOALKANES, CYCLICS, <5% N-HEXANE. CONTAINS:Cyclohexane 110-82-7 (10%); n-hexane 110-54-3 (<5%); PROPAN-2-OL

Safety Data Sheet

Precautionary statements (CLP)

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Hazard statements (CLP) : H222 - Extremely flammable aerosol.

H229 - Pressurised container: May burst if heated.

H315 - Causes skin irritation.

H319 - Causes serious eye irritation.

H336 - May cause drowsiness or dizziness.

H411 - Toxic to aquatic life with long lasting effects.

: P101 - If medical advice is needed, have product container or label at hand.

P102 - Keep out of reach of children.

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P211 - Do not spray on an open flame or other ignition source.

P251 - Do not pierce or burn, even after use.

P261 - Avoid breathing dust, fume, gas, mist, vapours, spray.

P273 - Avoid release to the environment.

P280 - Wear protective gloves, eye protection, face protection.

P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. P312 - Call a POISON CENTER, a doctor if you feel unwell.

P321 - Specific treatment (see supplemental first aid instruction on this label). P362+P364 - Take off contaminated clothing and wash it before reuse. P403+P233 - Store in a well-ventilated place. Keep container tightly closed.

P405 - Store locked up.

P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 $^{\circ}\text{C},\,122$

°F.

 $\ensuremath{\mathsf{P501}}$ - Dispose of Contents and container, to hazardous or special waste collection point, in

accordance with local, regional, national and/or international regulation.

UFI : JTH5-C0KA-N007-AWH8

2.3. Other hazards

Other hazards not contributing to the classification : The product does not meet the PBT and vPvB classification criteria.

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Comments : Description: Cleaner

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
HYDROCARBONS, C6-C7, N-ALKANES, ISOALKANES, CYCLICS, <5% N-HEXANE. CONTAINS:Cyclohexane 110-82-7 (10%); n-hexane 110-54-3 (<5%)	(CAS-No.) 92128-66-0 (EC-No.) 921-024-6 (REACH-no) 01-2119475514-35	25 – 50	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
Ethanol	(CAS-No.) 64-17-5 (EC-No.) 200-578-6 (EC Index-No.) 603-002-00-5 (REACH-no) 01-2119457610-43	10 – 25	Flam. Liq. 2, H225
DIMETHOXYETHANE	(CAS-No.) 109-87-5 (EC-No.) 203-714-2 (REACH-no) 01-2119664781-31	10 – 25	Flam. Liq. 2, H225

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

PROPAN-2-OL	(CAS-No.) 67-63-0 (EC-No.) 200-661-7 (EC Index-No.) 603-117-00-0 (REACH-no) 01-2119457558-25	10 – 25	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
KOOLSTOFDIOXIDE	(CAS-No.) 124-38-9 (EC-No.) 204-696-9	2.5 – 10	Press. Gas (Ref. Liq.), H281

Comments : Aliphatic hydrocarbons: >=30%

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation : If unconscious, place in the recovery position and seek medical advice. Also transport the

person in this position.

First-aid measures after skin contact : Wash immediately with plenty of soap and water. Rinse well.

First-aid measures after eye contact : Immediately rinse with water for a prolonged period while holding the eyelids wide open.

Consult an eye specialist.

First-aid measures after ingestion : Do NOT induce vomiting. Seek urgent medical help.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : No available data.

4.3. Indication of any immediate medical attention and special treatment needed

No additional data.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Carbon dioxide (CO2), powder, alcohol-resistant foam, water spray.

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Reactivity in case of fire : No additional information available.

5.3. Advice for firefighters

Protection during firefighting : Self-contained breathing apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Use personal protective equipment as required. Keep unprotected people away.

6.1.1. For non-emergency personnel

No additional information available

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Do not allow into drains or water courses. In case of contamination of soil or water bodies notify the competent authorities. Do not contaminate ground and surface water.

6.3. Methods and material for containment and cleaning up

Other information : Ensure adequate air ventilation. Do not flush with water or aqueous cleansing agents.

6/8/2020 (Version: 3.1) EN (English) 3/12

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

6.4. Reference to other sections

Stable under recommended handling and storage conditions (see section 7). For further information refer to section 8: "Exposure controls/personal protection". For disposal of residues refer to section 13: Disposal considerations" ".

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed

: Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Store away from heat. Take precautionary measures against static discharge. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use. Provide sufficient air exchange and/or exhaust.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures

: Store tightly closed in a dry and cool place.

Storage conditions

: Keep cool. The government provisions with regard to the storage of compressed gas

packings must be observed.

Heat and ignition sources

: Protect from heat and direct sunlight.

Information on mixed storage

observed.

7.3. Specific end use(s)

No additional information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Ethanol (64-17-5)		
Netherlands - Occupational Exposure Limits		
Local name	Ethanol	
Grenswaarde TGG 8H (mg/m³)	260 mg/m³	
Grenswaarde TGG 8H (ppm)	35 ppm	
Grenswaarde TGG 15MIN (mg/m³)	1900 mg/m³	
Grenswaarde TGG 15MIN (ppm)	990 ppm	
MAC C (mg/m³)	3800 mg/m³ Short time value (ppm) : 2000	
MAC C (ppm)	1000 ppm Long term (mg/m³) : 1900	
Remark (MAC)	H (Huidopname) Stoffen die relatief gemakkelijk door de huid kunnen worden opgenomen, hetgeen een substantiële bijdrage kan betekenen aan de totale inwendige blootstelling, hebben in de lijst een H-aanduiding. Bij deze stoffen moeten naast maatregelen tegen inademing ook adequate maatregelen ter voorkoming van huidcontact worden genomen.	
Regulatory reference	Arbeidsomstandighedenregeling 2018	

DIMETHOXYETHANE (109-87-5)	
Netherlands - Occupational Exposure Limits	
Grenswaarde TGG 8H (mg/m³) 3200 mg/m³	
Grenswaarde TGG 8H (ppm)	1000 ppm
Grenswaarde TGG 15MIN (mg/m³)	6400 mg/m³
Grenswaarde TGG 15MIN (ppm) 2000 ppm	

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

PROPAN-2-OL (67-63-0)	
EU - Occupational Exposure Limits	
IOELV TWA (mg/m³) 650 mg/m³	
IOELV TWA (ppm) 250 ppm	
Netherlands - Occupational Exposure Limits	
TRGS 903 Biological limit values 650 mg/m³, 250 ppm	

KOOLSTOFDIOXIDE (124-38-9)		
EU - Occupational Exposure Limits		
Local name	Carbon dioxide	
IOELV TWA (mg/m³)	9000 mg/m³	
IOELV TWA (ppm)	5000 ppm	
Regulatory reference COMMISSION DIRECTIVE 2006/15/EC		
Netherlands - Occupational Exposure Limits		
Local name	Kooldioxide	
Grenswaarde TGG 8H (mg/m³)	9000 mg/m³	
Grenswaarde TGG 8H (ppm) 5000 ppm		
Regulatory reference	Arbeidsomstandighedenregeling 2018	

HYDROCARBONS, C6-C7, N-ALKANES, ISOALKANES, CYCLICS, <5% N-HEXANE. CONTAINS: Cyclohexane 110-82-7 (10%); n-hexane 110-54-3 (<5%) (92128-66-0) **Netherlands - Occupational Exposure Limits** MAC C (mg/m³) 1200 mg/m³ Short time value (mg/m³)

PROPAN-2-OL (67-63-0)	
DNEL/DMEL (Workers)	
Long-term - systemic effects, dermal 888 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation 500 mg/m³	
DNEL/DMEL (General population)	
Long-term - systemic effects,oral 26 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	89 mg/m³
Long-term - systemic effects, dermal	319 mg/kg bodyweight/day

HYDROCARBONS, C6-C7, N-ALKANES, ISOALKANES, CYCLICS, <5% N-HEXANE. CONTAINS:Cyclohexane 110-82-7 (10%); n-hexane 110-54-3 (<5%) (92128-66-0)		
DNEL/DMEL (Workers)		
Long-term - systemic effects, dermal	773 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	2035 mg/m³	
DNEL/DMEL (General population)		
Long-term - systemic effects,oral	699 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	608 mg/m³	
Long-term - systemic effects, dermal	699 mg/kg bodyweight/day	

Additional information : The basis of the information is the data that were valid when compiled.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

8.2. Exposure controls

Appropriate engineering controls:

Keep away from food, drink and animal feeding stuffs. Take off immediately all contaminated clothing. Wash hands before breaks and after work. Do not breathe gas/fumes/vapour/spray. When handling product, avoid contact with skin and eyes.

Hand protection:

Solvent-resistant gloves. Choose glove material taking into account the penetration times, the permeation degrees and the degradation. Since the product consists of several substances, the durability of the glove material cannot be estimated and needs to be tested before use. Choosing the proper glove is a decision that depends not only on the type of material, but also on other quality features, which differ for each manufacturer. For continuous contact, we recommend gloves with a breakthrough time of at least 240 minutes, with a breakthrough time of more than 480 minutes being preferred. We recommend the same for short-term work or splash protection. We are aware that suitable gloves that provide this level of protection may not be available. In that case, a shorter breakthrough time may be acceptable, as long as the procedures for appropriate maintenance and timely replacement are followed. The thickness of the glove is not a good measure of the glove's resistance to a chemical, as it depends on the exact composition of the material the gloves are made of.

Туре	Material	Permeation	Thickness (mm)	Penetration	Standard
	` '	5 (> 240 minutes), 6 (> 480 minutes)	≥ 0,5 mm		

Eye protection: Safety glasses Type Use Characteristics Standard Safety goggles, Protective goggles EN 166

Skin and body protection:

Wear suitable protective clothing. EN-13034/6

Respiratory protection:			
Device	Filter type	Condition	Standard
	Type AX - Low-boiling (<65 °C) organic compounds, Type P2, Filter AX (brown), Filter A2/B2	Wear suitable respiratory equipment in case of insufficient ventilation	

Personal protective equipment symbol(s):





SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Gas Appearance : Aerosol. Colour Colourless. Odour Characteristic. Odour threshold No data available рΗ No data available Relative evaporation rate (butylacetate=1) No data available No data available Melting point Freezing point : No data available Boiling point : 42.3 °C

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Flash point : -18 °C

Auto-ignition temperature : The product does not ignite on its own.

Decomposition temperature : No data available Flammability (solid, gas) : Not applicable. Vapour pressure : 440 hPa at 20 °C

Relative vapour density at 20 °C : No data Relative density : No data

Density : 0.79 g/cm³ at 20 °C
Solubility : Practically not miscible.
Organic solvent:96,0%

Partition coefficient n-octanol/water (Log Pow) : No data

Viscosity, kinematic : No data available

Viscosity, dynamic : No data

Explosive properties : The product is not explosive, but the formation of explosive vapor / air mixtures is possible.

Oxidising properties : No data available Lower explosive limit (LEL) : 0.8 vol % Upper explosive limit (UEL) : 19.9 vol %

9.2. Other information

VOC content : 758.4 g/l VOC-CH: 96,00%

Other properties : Ignition temperature: 200 °C. Solids content: 14,4 %.

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available.

10.2. Chemical stability

No degradation when used as directed.

10.3. Possibility of hazardous reactions

No dangerous reactions known.

10.4. Conditions to avoid

No additional information available.

10.5. Incompatible materials

No additional information available.

10.6. Hazardous decomposition products

No hazardous decomposition products known.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Based on available data, the classification criteria are not met
Acute toxicity (dermal) : Based on available data, the classification criteria are not met
Acute toxicity (inhalation) : Based on available data, the classification criteria are not met

PROPAN-2-OL (67-63-0)	
LD50 oral rat 5840 mg/kg	
LD50 dermal rabbit	13900 mg/kg
LC50 inhalation rat (mg/l)	25 mg/l 6h

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

HYDROCARBONS, C6-C7, N-ALKANES, ISOALKANES, CYCLICS, <5% N-HEXANE. CONTAINS:Cyclohexane 110-82-7 (10%); n-hexane 110-54-3 (<5%) (92128-66-0)	
LD50 oral rat > 5840 mg/kg	
LD50 dermal rabbit	> 2920 mg/kg
LC50 inhalation rat (mg/l) > 25 mg/l/4h	

Skin corrosion/irritation : Causes skin irritation. pH: No data available

Serious eye damage/irritation : Causes serious eye irritation.

pH: No data available

Respiratory or skin sensitisation : Based on available data, the classification criteria are not met Germ cell mutagenicity : Based on available data, the classification criteria are not met Carcinogenicity : Based on available data, the classification criteria are not met

Reproductive toxicity : Based on available data, the classification criteria are not met

STOT-single exposure : May cause drowsiness or dizziness.

STOT-repeated exposure : Based on available data, the classification criteria are not met

Aspiration hazard : May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short-term

acute)

Hazardous to the aquatic environment, long-term $% \label{eq:control} % \label{eq:control}$

(chronic)

: Not classified

: Toxic to aquatic life with long lasting effects.

Ultra Degreaser Spray (500ml)	
Additional information	Toxic to fish.

PROPAN-2-OL (67-63-0)	
LC50 fish 1 9640 mg/l	
LC50 other aquatic organisms 1	9714 mg/l 24h
LOEC (chronic)	1000 mg/l algae (8days)

HYDROCARBONS, C6-C7, N-ALKANES, ISOALKANES, CYCLICS, <5% N-HEXANE. CONTAINS:Cyclohexane 110-82-7 (10%); n-hexane 110-54-3 (<5%) (92128-66-0)		
LC50 fish 1	11.4 mg/l 96h	
EC50 Daphnia 1	3 mg/l 48h	
EC50 72h algae (1)	30 – 100 mg/l	
LOEC (chronic)	0.32 mg/l daphnia	
NOEC (chronic)	3 mg/l algae 72h	
NOEC chronic crustacea	0.17 mg/l	

12.2. Persistence and degradability

Ultra Degreaser Spray (500ml)	
Persistence and degradability	No additional information available.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

12.3. Bioaccumulative potential

Ultra Degreaser Spray (500ml)		
Partition coefficient n-octanol/water (Log Pow) No data		
Bioaccumulative potential	No additional information available.	

12.4. Mobility in soil

Ultra Degreaser Spray (500ml)	
Mobility in soil	No supplementary information available

12.5. Results of PBT and vPvB assessment

Ultra Degreaser Spray (500ml)	
Results of PBT assessment	The product does not meet the PBT and vPvB classification criteria

12.6. Other adverse effects

Other adverse effects Additional information

Toxic for aquatic organisms, may have longterm hazardous effects in aquatic environment Hazardous to water (WGK 2(D)Self classification) Additional information

: No additional information available.

: Waterbezwaarlijkheid (NL): A (2)

: danger for water. Do not allow material to contaminate ground water system. Do not flush into surface water or sewer system. Danger of drinking-water pollution (ground water). Also poisonous to fish and plankton in surface water. Toxic to aquatic organisms.

: Waterbezwaarlijkheid (NL): A (2)

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods Product/Packaging disposal recommendations HP Code

- : Do not dispose of with domestic waste. Do not discharge into drains.
- : Disposal must be done according to official regulations.
- : HP3 "Flammable:"
- flammable liquid waste: liquid waste having a flash point below 60 °C or waste gas oil, diesel and light heating oils having a flash point > 55 °C and ≤ 75 °C;
- flammable pyrophoric liquid and solid waste: solid or liquid waste which, even in small quantities, is liable to ignite within five minutes after coming into contact with air;
- flammable solid waste: solid waste which is readily combustible or may cause or contribute to fire through friction;
- flammable gaseous waste: gaseous waste which is flammable in air at 20 $^{\circ}\text{C}$ and a standard pressure of 101.3 kPa;
- water reactive waste: waste which, in contact with water, emits flammable gases in dangerous quantities;
- other flammable waste: flammable aerosols, flammable self-heating waste, flammable organic peroxides and flammable self-reactive waste.
- HP4 "Irritant skin irritation and eye damage:" waste which on application can cause skin irritation or damage to the eye.
- HP5 "Specific Target Organ Toxicity (STOT)/Aspiration Toxicity:" waste which can cause specific target organ toxicity either from a single or repeated exposure, or which cause acute toxic effects following aspiration.

HP14 - "Ecotoxic:" waste which presents or may present immediate or delayed risks for one or more sectors of the environment

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

ADR	IMDG	IATA	ADN	RID
14.1. UN number				
UN 1950	UN 1950	UN 1950	UN 1950	Not regulated

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

14.2. UN proper shippin	g name			
AEROSOLS	AEROSOLS	Aerosols, flammable	AEROSOLS	Not regulated
Transport document descr	iption			
UN 1950 AEROSOLS, 2.1, (D), ENVIRONMENTALLY HAZARDOUS	UN 1950 AEROSOLS, 2.1, MARINE POLLUTANT/ENVIRONME NTALLY HAZARDOUS	UN 1950 Aerosols, flammable, 2.1, ENVIRONMENTALLY HAZARDOUS	UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY HAZARDOUS	Not regulated
14.3. Transport hazard	class(es)			
2.1	2.1	2.1	2.1	Not regulated
2	2	2	**************************************	Not regulated
14.4. Packing group				
Not applicable	Not applicable	Not applicable	Not applicable	Not regulated
14.5. Environmental haz	ards			
Dangerous for the environment : Yes	Dangerous for the environment : Yes Marine pollutant : Yes	Dangerous for the environment : Yes	Dangerous for the environment : Yes	Not regulated
Environmentally hazardous	substances: , Naphtha (petrole	um), hydrotreated, light.		

14.6. Special precautions for user

Special transport precautions : Aerosol warning

Overland transport

Classification code (ADR) : 5F
Limited quantities (ADR) : 1I
Excepted quantities (ADR) : E0
Transport category (ADR) : 2
Tunnel restriction code (ADR) : D

Transport by sea

Limited quantities (IMDG) : 1 L

Excepted quantities (IMDG) : E0

EmS-No. (Fire) : F-D

EmS-No. (Spillage) : S-U

Stowage category (IMDG) : None

Stowage and handling (IMDG) : SW1, SW22

Segregation (IMDG) : SG69

Air transport

No data available

Inland waterway transport

Classification code (ADN) : 5F
Limited quantities (ADN) : 1 L
Excepted quantities (ADN) : E0
Number of blue cones/lights (ADN) : 1

Rail transport Not regulated

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

VOC content : 758.4 g/l VOC-CH: 96,00%

Other information, restriction and prohibition

regulations

: Qualifying quantity (tonnes) for applications of requirements for low-threshold devices: 200 t. Qualifying quantity (tonnes) for application of requirements for high-threshold devices: 500

t.

Directive 2012/18/EU (SEVESO III)

Seveso Additional information : E2 : Hazardous to the Aquatic Environment in Category Chronic 2 . P3b Flammable

aerosol

15.1.2. National regulations

Klasse NK: 75 -< 100 %

Netherlands

SZW-lijst van kankerverwekkende stoffen

SZW-lijst van mutagene stoffen

NIET-limitatieve lijst van voor de voortplanting

giftige stoffen – Borstvoeding

NIET-limitatieve lijst van voor de voortplanting

giftige stoffen - Vruchtbaarheid

NIET-limitatieve lijst van voor de voortplanting

 $giftige\ stoffen-Ontwikkeling$

: Ethanol is listed

: None of the components are listed

: Ethanol is listed

: Ethanol is listed

: Ethanol is listed

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Abbreviations and acronyms:		
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road	
IMDG	International Maritime Dangerous Goods	
IATA	International Air Transport Association	
CAS-No.	Chemical Abstract Service number	
DNEL	Derived-No Effect Level	
LC50	Median lethal concentration	
LD50	Median lethal dose	
PBT	Persistent Bioaccumulative Toxic	

Full text of H- and EUH-statements:		
Aquatic Chronic 2 Hazardous to the aquatic environment — Chronic Hazard, Category 2		
Asp. Tox. 1	Aspiration hazard, Category 1	
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2	
Flam. Liq. 2	Flammable liquids, Category 2	

6/8/2020 (Version: 3.1) EN (English) 11/12

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Gases under pressure : Refrigerated liquefied gas
Skin corrosion/irritation, Category 2
Specific target organ toxicity — Single exposure, Category 3, Narcosis
Extremely flammable aerosol.
Highly flammable liquid and vapour.
Pressurised container: May burst if heated.
Contains refrigerated gas; may cause cryogenic burns or injury.
May be fatal if swallowed and enters airways.
Causes skin irritation.
Causes serious eye irritation.
May cause drowsiness or dizziness.
Toxic to aquatic life with long lasting effects.

SDS EU (REACH Annex II)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.