

BANDENSCHUIM

Page: 1

Compilation date: 13-10-2014

Revision No: 1

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: BANDENSCHUIM

Product code: 4150

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC35: Washing and cleaning products (including solvent based products).

1.3. Details of the supplier of the safety data sheet

Company name: ProPart International B.V.

Molenakker 3

Reuver 5953 TW

The Netherlands

Tel: +31 (0) 77 476 2368 **Fax:** +31 (0) 77 476 2424

Email: info@propart-international.com

1.4. Emergency telephone number

Emergency tel: +31 (0) 77 476 2368 (08.30-17.00)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Flam. Aerosol 1: H222; Eye Irrit. 2: H319; -: H229

Most important adverse effects: Extremely flammable aerosol. Pressurised container: May burst if heated. Causes

serious eye irritation.

2.2. Label elements

Label elements:

Hazard statements: H222: Extremely flammable aerosol.

H229: Pressurised container: May burst if heated

H319: Causes serious eye irritation.

Hazard pictograms: GHS02: Flame

GHS07: Exclamation mark





Signal words: Danger

Precautionary statements: P501: Dispose of contents/container to an approved waste disposal according to

BANDENSCHUIM

Page: 2

local/regional/national/international regulations.

P101: If medical advice is needed, have product container or label at hand.

P102: Keep out of reach of children.

P103: Read label before use.

P260: Do not breathe dust/fumes/gas/mist/vapours/spray.

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P251: Do not pierce or burn, even after use.

P211: Do not spray on an open flame or other ignition source.

P410+412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

2.3. Other hazards

Other hazards: In use, may form flammable / explosive dust-air mixture.

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

PROPAN-2-OL

| EINECS | CAS | PBT / WEL | CLP Classification | Percent |
|------------|----------|--|--|---------|
| 200-661-7 | 67-63-0 | - | Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336 | 7.500% |
| PROPANE | | | | |
| 200-827-9 | 74-98-6 | Substance with a Community workplace exposure limit. | Flam. Gas 1: H220; Press. Gas: H280 | 3.750% |
| BUTANE | | | | |
| 203-448-7 | 106-97-8 | Substance with a Community workplace exposure limit. | Flam. Gas 1: H220; Press. Gas: H280 | 3.750% |
| ISOBUTANE | | | | |
| 200-857-2 | 75-28-5 | Substance with a Community workplace exposure limit. | Flam. Gas 1: H220; Press. Gas: H280 | 3.750% |
| AMMONIA 25 | % | | | |
| - | - | - | Aquatic Acute 1: H400; Skin Corr. 1B: H314 | 0.550% |

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash

immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. If irritation persists, consult a doctor.

BANDENSCHUIM

Page: 3

Ingestion: Drink plenty of water and provide fresh air. Call a doctor immediately.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Move to

fresh air in case of accidental inhalation of vapours. In case of complaints consult

doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness. **Ingestion:** There may be irritation of the throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray

to cool containers. Carbon dioxide. Dry chemical powder. Water spray. Alcohol resistant

foam. Do not use water jet.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Highly flammable. In combustion emits toxic fumes. May form flammable / explosive

dust-air mixture.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Notify the police and fire

brigade immediately. Eliminate all sources of ignition.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Transfer to a closable, labelled salvage container for disposal by an appropriate

method. Do not use equipment in clean-up procedure which may produce sparks.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS. Refer to section 13 of SDS.

BANDENSCHUIM

Page: 4

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.

Do not handle in a confined space. Avoid the formation or spread of mists in the air.

Smoking is forbidden.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep away from sources of ignition. Keep container

tightly closed. Keep away from direct sunlight. Prevent the build up of electrostatic

charge in the immediate area. Ensure lighting and electrical equipment are not a source

of ignition.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

PROPAN-2-OL

Workplace exposure limits:

Respirable dust

| State | 8 hour TWA | 15 min. STEL | 8 hour TWA | 15 min. STEL |
|----------|------------|--------------|------------|--------------|
| UK | 999 mg/m3 | 1250 mg/m3 | - | - |
| PROPANE | | | | |
| UK | 1800 mg/m3 | 7200 mg/m3 | - | - |
| BUTANE | | | | |
| UK | 1450 mg/m3 | 1810 mg/m3 | - | - |
| SOBUTANE | | | | |
| UK | 2400 mg/m3 | 9600 mg/m3 | - | - |

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. Ensure lighting and electrical

equipment are not a source of ignition.

Respiratory protection: Respiratory protection not required.

Hand protection: Not applicable.Eye protection: Not applicable.Skin protection: Not applicable.

BANDENSCHUIM

Page: 5

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Aerosol

Colour: According to product specification.

Odour: Characteristic odour

Evaporation rate: Not applicable.

Solubility in water: Not / slightly miscible.

Viscosity: No data available.

Boiling point/range°C: Not applicable. **Melting point/range°C:** No data available.

Flammability limits %: lower: 2,0 upper: 12,0

Flash point°C: <0 Part.coeff. n-octanol/water: No data available.

Autoflammability°C: No autoignition Vapour pressure: 3500 hPa

Relative density: No data available. pH: No data available.

VOC g/I: 396,5

9.2. Other information

Other information: Température d'inflammation: 425°C. Density: 0,901 g/cm3. Solvent content: organic

solvent: 20,4%. EU-VOC in%: 20,36%. Water: 59,6%.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions. Stable at room temperature.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat. Hot surfaces. Sources of ignition. Flames.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

BANDENSCHUIM

Page: 6

Hazardous ingredients:

PROPAN-2-OL

| IVN | RAT | LD50 | 1088 | mg/kg |
|-----|-----|------|------|-------|
| ORL | MUS | LD50 | 3600 | mg/kg |
| ORL | RAT | LD50 | 5045 | mg/kg |
| SCU | MUS | LDLO | 6 | gm/kg |

AMMONIA 25%

| ORAL | RAT | LD50 | 350 | mg/kg |
|---------|-----|---------|-----|-------|
| VAPOURS | RAT | 4H LC50 | 5,1 | mg/kg |

Relevant hazards for substance:

| Hazard | Route | Basis | |
|-------------------------------|-------|-----------------------|--|
| Serious eye damage/irritation | OPT | Hazardous: calculated | |

Symptoms / routes of exposure

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness. **Ingestion:** There may be irritation of the throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values:

| Species | Test | Value | Units |
|---------------|----------|-------|-------|
| FISH | 96H LC50 | 4200 | mg/l |
| Daphnia magna | 48H EC50 | 13299 | mg/l |
| CAS 67-63-0 | - | - | - |
| AMMONIA 25% | - | - | - |
| Daphnia magna | LC50 | 25,4 | mg/l |

Hazardous ingredients:

AMMONIA 25%

| Daphnia magna | LC50 | 25,4 | mg/l |
|---------------|------|------|------|

12.2. Persistence and degradability

Persistence and degradability: No data available.

BANDENSCHUIM

Page: 7

12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

12.4. Mobility in soil

Mobility: No data available.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Water hazard class (NL) 9: Harmful to aquatic organisms in the water. Water hazard

class 1 (D) (Self-assessment): hazardous for water.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal

company. Must not be disposed together with household garbage or into the sewage

system.

Waste code number: 20 01 13

Disposal of packaging: Uncontaminated packaging can be recycled.

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1950

14.2. UN proper shipping name

Shipping name: AEROSOLS

14.3. Transport hazard class(es)

Transport class: 2

14.4. Packing group

14.5. Environmental hazards

Environmentally hazardous: No Marine pollutant: No

14.6. Special precautions for user

Special precautions: Warning: Gases. EMS number:F-D,S-U. Segregation groups: Alkalis.

Tunnel code: D

Transport category: 2

BANDENSCHUIM

Page: 8

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Regulation (EC) No. 1907/2006.

This safety data sheet is prepared in accordance with Commission Regulation (EC) No

1272/2008.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: H220: Extremely flammable gas.

H222: Extremely flammable aerosol.

H225: Highly flammable liquid and vapour.

H229: Pressurised container: May burst if heated

H314: Causes severe skin burns and eye damage.

H319: Causes serious eye irritation.

H336: May cause drowsiness or dizziness.

H400: Very toxic to aquatic life.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive

and shall be used only as a guide. This company shall not be held liable for any

damage resulting from handling or from contact with the above product.