

INOX SPRAY (400ML)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830
Issue date: 12/8/2020 Revision date: 10/15/2020 Supersedes version of: 11/6/2019 Version: 7.1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Trade name : INOX SPRAY (400ML)
UFI : 9EMF-G0HE-800F-0MUV
Product code : 5281

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Professional use

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Pro Part International
Molenakker 3
5953 TW Reuver - Nederland
T +31 (0) 77 476 2204
info@propart-international.com - www.propart-international.com

1.4. Emergency telephone number

No additional information available

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol, Category 1	H222;H229
Serious eye damage/eye irritation, Category 2	H319
Specific target organ toxicity — Single exposure, Category 3, Narcosis	H336
Full text of H statements : see section 16	


Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



Signal word (CLP)

: Danger

Contains

: ACETONE; N-BUTYL ACETATE; BUTAN-1-OL; N-BUTANOL

Hazard statements (CLP)

: H222 - Extremely flammable aerosol.

H229 - Pressurised container: May burst if heated.

H319 - Causes serious eye irritation.

H336 - May cause drowsiness or dizziness.

INOX SPRAY (400ML)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Precautionary statements (CLP)	: P101 - If medical advice is needed, have product container or label at hand. P102 - Keep out of reach of children. P210 - Keep away from heat, hot surfaces, open flames, sparks. No smoking. P211 - Do not spray on an open flame or other ignition source. P251 - Do not pierce or burn, even after use. P260 - Do not breathe dusts or mists. P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C, 122 °F. P501 - Dispose of Contents and container, to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.
EUH-statements	: EUH066 - Repeated exposure may cause skin dryness or cracking.
Extra phrases	: Without adequate ventilation formation of explosive mixtures may be possible.

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Comments : Mixture of the following substances with non-hazardous additions

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
DIMETHYLETHER substance with a Community workplace exposure limit	(CAS-No.) 115-10-6 (EC-No.) 204-065-8 (EC Index-No.) 603-019-00-8 (REACH-no) 01-2119472128-37	25 – 50	Flam. Gas 1A, H220 Press. Gas (Comp.), H280
ACETONE substance with a Community workplace exposure limit	(CAS-No.) 67-64-1 (EC-No.) 200-662-2 (EC Index-No.) 606-001-00-8 (REACH-no) 01-2119471330-49	20 – 25	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
2-METHOXY-1-METHYLETHYL ACETATE substance with a Community workplace exposure limit	(CAS-No.) 108-65-6 (EC-No.) 203-603-9 (EC Index-No.) 607-195-00-7 (REACH-no) 01-2119475791-29	10 – 12.5	Flam. Liq. 3, H226
PROPANE	(CAS-No.) 74-98-6 (EC-No.) 200-827-9 (EC Index-No.) 601-003-00-5 (REACH-no) 01-2119475527-28	5 – 10	Flam. Gas 1A, H220 Press. Gas
N-BUTYL ACETATE substance with a Community workplace exposure limit	(CAS-No.) 123-86-4 (EC-No.) 204-658-1 (EC Index-No.) 607-025-00-1 (REACH-no) 01-2119485493-29	5 – 10	Flam. Liq. 3, H226 STOT SE 3, H336
BUTANE substance with a Community workplace exposure limit	(CAS-No.) 106-97-8 (EC-No.) 203-448-7 (EC Index-No.) 601-004-00-0 (REACH-no) 01-2119474691-32	5 – 10	Flam. Gas 1A, H220 Press. Gas (Comp.), H280
ALUMINIUM POWDER (PYROPHORIC)	(CAS-No.) 7429-90-5 (EC-No.) 231-072-3 (EC Index-No.) 013-001-00-6	< 2.5	Water-react. 2, H261 Pyr. Liq. 1, H250

INOX SPRAY (400ML)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

BUTAN-1-OL; N-BUTANOL substance with a Community workplace exposure limit	(CAS-No.) 71-36-3 (EC-No.) 200-751-6 (EC Index-No.) 603-004-00-6 (REACH-no) 01-2119484630-38	< 2.5	Flam. Liq. 3, H226 Acute Tox. 4 (Oral), H302 STOT SE 3, H335 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H336
XYLENE substance with a Community workplace exposure limit	(CAS-No.) 1330-20-7 (EC-No.) 215-535-7 (EC Index-No.) 601-022-00-9 (REACH-no) 01-2119488216-32	< 2.5	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304
NITROCELLULOSE	(CAS-No.) 9004-70-0	< 2.5	Flam. Sol. 1, H228

Comments : aluminium powder (stabilised) CAS 7429-90-5, EINECS 231-072-3, INDEX 013-002-00-1
:Note T

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation : Allow affected person to breathe fresh air. In all cases of doubt, or when symptoms persist, seek medical attention.

First-aid measures after skin contact : Generally the product does not irritate the skin.

First-aid measures after eye contact : Rinse opened eye for several minutes under running water. If eye irritation persists and/or symptoms, obtain medical attention.

First-aid measures after ingestion : Drink plenty of water. Move to fresh air. Get immediate medical advice/attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : No additional information available.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : carbon dioxide. Dry powder. Water spray. Fight larger fires with water spray or alcohol resistant foam.

5.2. Special hazards arising from the substance or mixture

Reactivity in case of fire : On heating or during combustion toxic fumes are released.

5.3. Advice for firefighters

Protection during firefighting : Breathing equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Provide adequate ventilation. Keep away from ignition sources.

INOX SPRAY (400ML)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

6.1.1. For non-emergency personnel

- Protective equipment : Breathing apparatus.
Emergency procedures : Use personal protective equipment as required. Keep unprotected people away.

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Do not contaminate ground and surface water. Do not discharge into drains.

6.3. Methods and material for containment and cleaning up

- Methods for cleaning up : For disposal of contaminated materials refer to section 13 : "Disposal considerations".
Ensure that there is a suitable ventilation system.

6.4. Reference to other sections

Stable under recommended handling and storage conditions (see section 7). Concerning personal protective equipment to use, see section 8. For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Provide sufficient air exchange and/or exhaust. Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Keep respiratory protective equipment available. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Keep tanks tightly closed.
Storage conditions : The government provisions with regard to the storage of compressed gas packings must be observed.
Information on mixed storage : Not applicable.
Storage area : Category 2B.

7.3. Specific end use(s)

No additional information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

DIMETHYLETHER (115-10-6)	
EU - Indicative Occupational Exposure Limit (IOEL)	
IOEL TWA	950 mg/m ³
IOEL TWA [ppm]	495 ppm
IOEL STEL	1500 mg/m ³
IOEL STEL [ppm]	782 ppm

ACETONE (67-64-1)

EU - Indicative Occupational Exposure Limit (IOEL)	
IOEL TWA	1210 mg/m ³
IOEL TWA [ppm]	500 ppm

INOX SPRAY (400ML)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

ACETONE (67-64-1)	
IOEL STEL	3620 mg/m ³
IOEL STEL [ppm]	1500 ppm

2-METHOXY-1-METHYLETHYL ACETATE (108-65-6)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	2-Methoxy-1-methylethylacetate
IOEL TWA	274 mg/m ³
IOEL TWA [ppm]	50 ppm
IOEL STEL	548 mg/m ³
IOEL STEL [ppm]	100 ppm
Notes	Skin
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
Netherlands - Occupational Exposure Limits	
Local name	1-Methoxy-2-propylacetaat
MAC-TGG (OEL TWA)	550 mg/m ³
Regulatory reference	Arbeidsomstandighedenregeling 2020

N-BUTYL ACETATE (123-86-4)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	n-Butyl acetate
IOEL TWA	724 mg/m ³
IOEL TWA [ppm]	150 ppm
IOEL STEL	966 mg/m ³
IOEL STEL [ppm]	200 ppm
Regulatory reference	COMMISSION DIRECTIVE (EU) 2019/1831

BUTANE (106-97-8)	
EU - Indicative Occupational Exposure Limit (IOEL)	
IOEL TWA	1450 mg/m ³
IOEL TWA [ppm]	600 ppm
IOEL STEL	1810 mg/m ³
IOEL STEL [ppm]	750 ppm
	Carcinogenic (if more than 0.1% 1,3-butadiene; buta-1,3-diene)

ALUMINIUM POWDER (PYROPHORIC) (7429-90-5)	
EU - Indicative Occupational Exposure Limit (IOEL)	
IOEL TWA	inhalable and respirable dust 10 en 4 mg/m ³

BUTAN-1-OL; N-BUTANOL (71-36-3)	
EU - Indicative Occupational Exposure Limit (IOEL)	
IOEL STEL	154 mg/m ³

INOX SPRAY (400ML)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

BUTAN-1-OL; N-BUTANOL (71-36-3)

IOEL STEL [ppm]	50 ppm
Notes	Sk

XYLENE (1330-20-7)

EU - Indicative Occupational Exposure Limit (IOEL)

Local name	Xylene, mixed isomers, pure
IOEL TWA	220 mg/m ³
IOEL TWA [ppm]	50 ppm
IOEL STEL	441 mg/m ³
IOEL STEL [ppm]	100 ppm
Notes	Sk;BMGV
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC

EU - Biological Limit Value (BLV)

BLV	650 Medium: Urine, Sampling time: Post shift, Parameter: Methyl Hippuric acid
-----	---

Netherlands - Occupational Exposure Limits

Local name	Xyleen, o-, m-, p-isomeren
MAC-TGG (OEL TWA)	210 mg/m ³
MAC-TGG (OEL TWA) [ppm]	47 ppm
MAC-15 (OEL STEL)	442 mg/m ³
MAC-15 (OEL STEL) [ppm]	100 ppm
Remark (MAC)	H (Huidopname) Stoffen die relatief gemakkelijk door de huid kunnen worden opgenomen, hetgeen een substantiële bijdrage kan betekenen aan de totale inwendige blootstelling, hebben in de lijst een H-aanduiding. Bij deze stoffen moeten naast maatregelen tegen inademing ook adequate maatregelen ter voorkoming van huidcontact worden genomen.
Regulatory reference	Arbeidsomstandighedenregeling 2020

8.1.2. Recommended monitoring procedures

Monitoring methods

Monitoring methods	No additional data, see chapter 7. The basis of the information is the data that were valid when compiled.
--------------------	--

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Keep away from food, drink and animal feedingstuffs. Take off immediately all contaminated clothing. Wash hands before breaks and after work. Do not breathe gas/fumes/vapour/spray. Avoid contact with eyes. Avoid contact with skin.

8.2.2. Personal protection equipment

Personal protective equipment:

Safety glasses. Gloves. Gas mask.

INOX SPRAY (400ML)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:

Safety glasses

8.2.2.2. Skin protection

Hand protection:

protective gloves. Butyl-rubber protective gloves. Choosing the proper glove is a decision that depends not only on the type of material, but also on other quality features, which differ for each manufacturer. Butyl rubber gloves with a thickness of 0.4 mm are resistant to: Acetone : 480 min. Butyl acetates : 60 min. Ethyl acetate : 170 min. Xylenes : 42 min. Butyl rubber gloves with a thickness of 0.4 mm are solvent resistant for 42 - 480 minutes. For safety reasons, we advise users and persons responsible for safety at work to assume a solvent resistance of 42 minutes. In view of the information in section 3 of this SDS, a longer resistance duration can be assumed in certain cases.

8.2.2.3. Respiratory protection

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device. A2/P3

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

No additional information available

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Gas
Colour	: Silver.
Odour	: Solvent.
Odour threshold	: Not determined.
Melting point	: Undefined
Freezing point	: Undefined
Boiling point	: Not applicable, as aerosol.
Flammability	: Not applicable
Explosive properties	: The product is not explosive, but the formation of explosive vapor / air mixtures is possible.
Explosive limits	: Not available
Lower explosive limit (LEL)	: 1.5 vol %
Upper explosive limit (UEL)	: 26.2 vol %
Flash point	: < 0 °C (< 32 °F) Not applicable, as aerosol.
Auto-ignition temperature	: 240 °C (464 ° F)
Decomposition temperature	: Not determined.
pH	: Not determined.
Viscosity, kinematic	: Not determined.
Viscosity, dynamic	: Not determined.
Solubility	: Water: 0.2 % Not miscible/Practically not miscible Organic solvent:93.3 %
Partition coefficient n-octanol/water (Log Kow)	: Not determined.
Vapour pressure	: 4000 hPa @ 20 °C (3000,2 mm Hg)
Vapour pressure at 50 °C	: Not available
Density	: 0.7 g/cm³ @ 20 °C (5,8 lbs/gal)

INOX SPRAY (400ML)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Relative density	: Not determined.
Relative vapour density at 20 °C	: Not available
Particle size	: Not applicable
Particle size distribution	: Not applicable
Particle shape	: Not applicable
Particle aspect ratio	: Not applicable
Particle aggregation state	: Not applicable
Particle agglomeration state	: Not applicable
Particle specific surface area	: Not applicable
Particle dustiness	: Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

Relative evaporation rate (butylacetate=1)	: Not applicable.
VOC content	: 683.2 g/l VOC-EU : 93,34 %
Other properties	: Solids content: 6,3%

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available.

10.2. Chemical stability

No decomposition when used according to regulations.

10.3. Possibility of hazardous reactions

No dangerous reactions known.

10.4. Conditions to avoid

No additional information available.

10.5. Incompatible materials

No additional information available.

10.6. Hazardous decomposition products

No hazardous decomposition products known.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

ACETONE (67-64-1)

LD50 oral rat	5800 mg/kg
LD50 dermal rabbit	> 15800 mg/kg
LC50 Inhalation - Rat	76 mg/l

INOX SPRAY (400ML)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

2-METHOXY-1-METHYLETHYL ACETATE (108-65-6)

LD50 oral rat	8530 mg/kg
LD50 dermal rabbit	> 5000 mg/kg
LC50 Inhalation - Rat	> 10000 mg/m ³ 4h

N-BUTYL ACETATE (123-86-4)

LD50 oral rat	10800 mg/kg
LD50 dermal rabbit	> 17600 mg/kg
LC50 Inhalation - Rat	> 21 mg/m ³ 4h

BUTAN-1-OL; N-BUTANOL (71-36-3)

LD50 oral rat	2292 mg/kg
LD50 dermal rabbit	3430 mg/kg
LC50 Inhalation - Rat	17000 mg/m ³ 4h

XYLENE (1330-20-7)

LD50 oral rat	3523 mg/kg
LD50 dermal rabbit	2000 mg/kg
LC50 Inhalation - Rat	29000 mg/m ³ 4h

Skin corrosion/irritation	: Based on available data, the classification criteria are not met pH: Not determined.
Serious eye damage/irritation	: Causes serious eye irritation. pH: Not determined.
Respiratory or skin sensitisation	: Based on available data, the classification criteria are not met
Germ cell mutagenicity	: Based on available data, the classification criteria are not met
Carcinogenicity	: Based on available data, the classification criteria are not met
Reproductive toxicity	: Based on available data, the classification criteria are not met
STOT-single exposure	: May cause drowsiness or dizziness.
STOT-repeated exposure	: Not classified
Aspiration hazard	: Based on available data, the classification criteria are not met

INOX SPRAY (400ML)

Viscosity, kinematic	Not determined.
----------------------	-----------------

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Not classified

INOX SPRAY (400ML)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

DIMETHYLETHER (115-10-6)

LC50 - Fish [1]	> 4000 mg/l
EC50 - Crustacea [1]	> 4000 mg/l
EC50 96h - Algae [1]	155 mg/l

ACETONE (67-64-1)

LC50 - Fish [1]	8300 mg/l
EC50 - Crustacea [1]	8450 mg/l Crustacean (water flea)
EC50 96h - Algae [1]	7200 mg/l

2-METHOXY-1-METHYLETHYL ACETATE (108-65-6)

LC50 - Fish [1]	100 – 180 mg/l
EC50 - Crustacea [1]	> 500 mg/l

BUTAN-1-OL; N-BUTANOL (71-36-3)

LC50 - Fish [1]	1376 mg/l
-----------------	-----------

XYLENE (1330-20-7)

LC50 - Fish [1]	13.5 mg/l
EC50 - Crustacea [1]	7.4 mg/l

12.2. Persistence and degradability

INOX SPRAY (400ML)

Persistence and degradability	No additional information available.
-------------------------------	--------------------------------------

12.3. Bioaccumulative potential

INOX SPRAY (400ML)

Partition coefficient n-octanol/water (Log Kow)	Not determined.
Bioaccumulative potential	No additional information available.

PROPANE (74-98-6)

Partition coefficient n-octanol/water (Log Pow)	2.76
---	------

12.4. Mobility in soil

INOX SPRAY (400ML)

Mobility in soil	No supplementary information available
Additional information	Germany - WGK List of Waters Hazards (AwSV) (Self classification) Class 1; Slightly hazardous to water. Do not discharge undiluted or in large quantities into groundwater, surface water or sewage.

12.5. Results of PBT and vPvB assessment

INOX SPRAY (400ML)

Results of PBT assessment	The product does not meet the PBT and vPvB classification criteria
---------------------------	--

INOX SPRAY (400ML)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

Other adverse effects : No additional information available




SECTION 13: Disposal considerations

13.1. Waste treatment methods

Sewage disposal recommendations : Do not dispose of with domestic waste. Do not discharge into drains.
Product/Packaging disposal recommendations : Disposal must be done according to official regulations.
European List of Waste (LoW) code : 08 01 11* - waste paint and varnish containing organic solvents or other dangerous substances
15 01 04 - metallic packaging

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA

ADR	IMDG	IATA
14.1. UN number or ID number		
UN 1950	UN 1950	UN 1950
14.2. UN proper shipping name		
AEROSOLS	AEROSOLS	Aerosols, flammable
Transport document description		
UN 1950 AEROSOLS, 2.1, (D)	UN 1950 AEROSOLS, 2.1	UN 1950 Aerosols, flammable, 2.1
14.3. Transport hazard class(es)		
2.1	2.1	2.1
		
14.4. Packing group		
Not applicable	Not applicable	Not applicable
14.5. Environmental hazards		
Dangerous for the environment : No	Dangerous for the environment : No Marine pollutant : No	Dangerous for the environment : No
Not applicable.		

14.6. Special precautions for user

Overland transport

Classification code (ADR) : 5F
Limited quantities (ADR) : 1I
Excepted quantities (ADR) : E0
Transport category (ADR) : 2
Tunnel restriction code (ADR) : D

Transport by sea

EmS-No. (Fire) : F-D

INOX SPRAY (400ML)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

EmS-No. (Spillage) : S-U
Stowage category (IMDG) : None
Stowage and handling (IMDG) : SW1, SW22
Segregation (IMDG) : SG69

Air transport

No data available

14.7. Maritime transport in bulk according to IMO instruments

IBC code : Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

The following restrictions are applicable according to Annex XVII of the REACH Regulation (EC) No 1907/2006:

Reference code	Applicable on	Entry title or description
40.	DIMETHYLETHER ; ACETONE ; 2-METHOXY-1-METHYLETHYL ACETATE ; PROPANE ; N-BUTYL ACETATE ; BUTANE ; ISOBUTANE (CONTAINS <0,1% BUTADIENE (203-450-8)) ; ALUMINIUM POWDER (PYROPHORIC) ; BUTAN-1-OL; N-BUTANOL ; XYLENE ; NITROCELLULOSE	Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or not.

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

VOC content : 683.2 g/l VOC-EU : 93,34 %

Other information, restriction and prohibition regulations : Qualifying quantity (tonnes) for application of requirements for high-threshold devices: 500 t.
Qualifying quantity (tonnes) for applications of requirements for low-threshold devices: 150 t.

Directive 2012/18/EU (SEVESO III)

Seveso Additional information : P3a Flammable aerosol

15.1.2. National regulations

Netherlands

SZW-lijst van kankerverwekkende stoffen : None of the components are listed

SZW-lijst van mutagene stoffen : None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Borstvoeding : None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Vruchtbaarheid : None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling : XYLENE is listed

15.2. Chemical safety assessment

Chemical safety assessments for substances in this preparation were not carried out

INOX SPRAY (400ML)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 16: Other information

Abbreviations and acronyms:

RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
IMDG	International Maritime Dangerous Goods
IATA	International Air Transport Association
CAS-No.	Chemical Abstract Service number
VOC	Volatile Organic Compounds
LC50	Median lethal concentration
LD50	Median lethal dose
PBT	Persistent Bioaccumulative Toxic
vPvB	Very Persistent and Very Bioaccumulative

Data sources : These data are based on the current state of our knowledge. However, they do not provide a guarantee of product properties and do not establish a contractual legal relationship.

Full text of H- and EUH-statements:

Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Gas 1A	Flammable gases, Category 1A
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Flam. Sol. 1	Flammable solids, Category 1
Press. Gas	Gases under pressure
Press. Gas (Comp.)	Gases under pressure : Compressed gas
Pyr. Liq. 1	Pyrophoric Liquids, Category 1
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
Water-react. 2	Substances and Mixtures which, in contact with water, emit flammable gases, Category 2
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H228	Flammable solid.
H229	Pressurised container: May burst if heated.

INOX SPRAY (400ML)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

H250	Catches fire spontaneously if exposed to air.
H261	In contact with water releases flammable gases.
H280	Contains gas under pressure; may explode if heated.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
EUH066	Repeated exposure may cause skin dryness or cracking.

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.