

SAFETY DATA SHEET
BODY COATING BLACK 500 ML

Page: 1

Compilation date: 01-06-2015

Revision date: 05-03-2018

Revision No: 57

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: BODY COATING BLACK 500 ML

Product code: 5452

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC9a: Coatings and paints, thinners, paint removers. PROC7: Industrial spraying
PROC11: Non industrial spraying ERC8a: Wide dispersive indoor use of processing
aids in open systems ERC8d: Wide dispersive outdoor use of processing aids in open
systems

1.3. Details of the supplier of the safety data sheet

Company name: ProPart International B.V.

Molenakker 3

Reuver

5953 TW

The Netherlands

Tel: +31 (0) 77 476 2368

Fax: +31 (0) 77 476 2424

Email: info@propart-international.com

1.4. Emergency telephone number

Emergency tel: +31 (0) 77 476 2368 (08.30-17.00)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Skin Sens. 1: H317; STOT SE 3: H336; Aquatic Chronic 3: H412; Eye Irrit. 2: H319; Flam.
Aerosol 1: H222; -: H229; -: EUH066

Most important adverse effects: Extremely flammable aerosol. Pressurised container: May burst if heated. Causes
serious eye irritation. May cause an allergic skin reaction. May cause drowsiness or
dizziness. Harmful to aquatic life with long lasting effects. Repeated exposure may
cause skin dryness or cracking.

2.2. Label elements

Label elements:

Hazard statements: H222: Extremely flammable aerosol.

H229: Pressurised container: May burst if heated

H319: Causes serious eye irritation.

[cont...]

SAFETY DATA SHEET

BODY COATING BLACK 500 ML

Page: 2

H317: May cause an allergic skin reaction.

H336: May cause drowsiness or dizziness.

H412: Harmful to aquatic life with long lasting effects.

EUH066: Repeated exposure may cause skin dryness or cracking.

Hazard pictograms: GHS02: Flame

GHS07: Exclamation mark



Signal words: Danger

Precautionary statements: P501: Dispose of contents/container to hazardous or special waste collection point.

P102: Keep out of reach of children.

P260: Do not breathe dust/fumes/gas/mist/vapours/spray.

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P251: Do not pierce or burn, even after use.

P211: Do not spray on an open flame or other ignition source.

P410+412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

N-BUTYL ACETATE

EINECS	CAS	PBT / WEL	CLP Classification	Percent
204-658-1	123-86-4	-	Flam. Liq. 3: H226; STOT SE 3: H336; -: EUH066	10-30%

PROPANE - REACH registered number(s): 01-2119486944-21-XXXX

200-827-9	74-98-6	Substance with a Community workplace exposure limit.	Flam. Gas 1: H220; Press. Gas: H280	10-30%
-----------	---------	--	-------------------------------------	--------

ACETONE

200-662-2	67-64-1	-	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336; -: EUH066	1-10%
-----------	---------	---	--	-------

[cont...]

SAFETY DATA SHEET

BODY COATING BLACK 500 ML

Page: 3

ETHYL ACETATE

205-500-4	141-78-6	-	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336; -: EUH066	1-10%
-----------	----------	---	---	-------

BUTANE - REACH registered number(s): 01-2119474691-32-XXXX

203-448-7	106-97-8	Substance with a Community workplace exposure limit.	Flam. Gas 1: H220; Press. Gas: H280	1-10%
-----------	----------	---	-------------------------------------	-------

ISOBUTANE

200-857-2	75-28-5	Substance with a Community workplace exposure limit.	Flam. Gas 1: H220; Press. Gas: H280	1-10%
-----------	---------	---	-------------------------------------	-------

HYDROCARBONS, C7-C9, N-ALKANES, ISOALKANES, CYCLICS - REACH registered number(s): 01-2119475515-33

-	-	-	STOT SE 3: H335; STOT SE 3: H336; Flam. Liq. 2: H225; Asp. Tox. 1: H304; Skin Irrit. 2: H315; Aquatic Chronic 2: H411	1-10%
---	---	---	--	-------

LOW BOILING POINT NAPHTHA - UNSPECIFIED - SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM.

265-199-0	64742-95-6	-	Asp. Tox. 1: H304; Flam. Liq. 3: H226; STOT SE 3: H335; Aquatic Chronic 2: H411	1-10%
-----------	------------	---	---	-------

ROSIN

232-475-7	8050-09-7	-	Skin Sens. 1: H317	1-10%
-----------	-----------	---	--------------------	-------

XYLENE

215-535-7	1330-20-7	-	Flam. Liq. 3: H226; Acute Tox. 4: H332; Acute Tox. 4: H312; Skin Irrit. 2: H315	1-10%
-----------	-----------	---	--	-------

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Wash immediately with plenty of soap and water.

Eye contact: Ensure adequate flushing of eyes by separating eyelids with the fingers. If symptoms persist, consult a doctor

Ingestion: Drink plenty of water and provide fresh air. Call a doctor immediately.

Inhalation: Provide fresh air. Consult a doctor. If unconscious and breathing is OK, place in the recovery position.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

[cont...]

SAFETY DATA SHEET
BODY COATING BLACK 500 ML

Page: 4

4.3. Indication of any immediate medical attention and special treatment needed

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Carbon dioxide. Dry chemical powder. Water spray. Fight larger fires with water spray or foam, which is resistant to alcohol. Do not use water jet.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: No data available.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Ensure adequate ventilation. Eliminate all sources of ignition.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Ensure adequate ventilation.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS. Refer to section 13 of SDS. See section 7 for information on safe handling

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Ensure there is sufficient ventilation of the area. Smoking is forbidden. Do not spray onto a naked flame or any incandescent material. Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50 °C i.e. electric lights. Do not pierce or burn, even after use. Keep ignition sources away. Protect against electrostatic charges.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed. Keep away from direct sunlight. Prevent the build up of electrostatic charge in the immediate area. The floor of the storage room must be impermeable to prevent the escape of liquids. Government regulations regarding the storage of pressurized containers must be observed.

[cont...]

SAFETY DATA SHEET
BODY COATING BLACK 500 ML

Page: 5

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

N-BUTYL ACETATE

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	724 mg/m3	966 mg/m3	-	-

PROPANE

UK	1800 mg/m3	7200 mg/m3	-	-
----	------------	------------	---	---

ACETONE

UK	1210 mg/m3	3620 mg/m3	-	-
----	------------	------------	---	---

ETHYL ACETATE

UK	200 ppm	400 ppm	-	-
----	---------	---------	---	---

BUTANE

UK	1450 mg/m3	1810 mg/m3	-	-
----	------------	------------	---	---

ISOBUTANE

UK	2400 mg/m3	9600 mg/m3	-	-
----	------------	------------	---	---

ROSIN

UK	0.05 mg/m3	0.15 mg/m3	-	-
----	------------	------------	---	---

XYLENE

UK	220 mg/m3	441 mg/m3	-	-
----	-----------	-----------	---	---

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. Keep away from foodstuffs, beverages and feed. Remove contaminated clothing immediately. Wash hands before breaks and at end of work. Do not inhale gases / fumes / aerosols.

Respiratory protection: Respiratory protection not required.

Hand protection: Protective gloves. The glove material has to be impermeable and resistant to the product / the substance / the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation. The selection of a suitable gloves does not only depend on the material, but also upon the

[cont...]

SAFETY DATA SHEET

BODY COATING BLACK 500 ML

Page: 6

quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to use. The exact break through time has to be found out by the glove manufacturer; observed.

Eye protection: Safety glasses.

Skin protection: Protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Aerosol

Colour: Black

Odour: Characteristic odour

Evaporation rate: Not applicable.

Solubility in water: Not / slightly miscible.

Viscosity: No data available.

Boiling point/range°C: Not applicable.

Melting point/range°C: No data available.

Flammability limits %: lower: 1,2

upper: 10,9

Flash point°C: <0

Part.coeff. n-octanol/water: No data available.

Autoflammability°C: No autoignition

Vapour pressure: 3500 hPa

Relative density: No data available.

pH: No data available.

VOC g/l: 593,7 g/l - EU-VOC in % 70,76%

9.2. Other information

Other information: Ignition temperature: 200°C. Density: 0,839 g/cm³. Solvent content: organic solvent: 62,9%. Content of solids: 37,1%.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

10.4. Conditions to avoid

Conditions to avoid: No data available.

10.5. Incompatible materials

Materials to avoid: No data available.

[cont...]

SAFETY DATA SHEET
BODY COATING BLACK 500 ML

Page: 7

10.6. Hazardous decomposition products

Haz. decomp. products: No data available.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

N-BUTYL ACETATE

ORL	MUS	LD50	6	gm/kg
ORL	RAT	LD50	10768	mg/kg

ACETONE

IVN	RAT	LD50	5500	mg/kg
ORL	MUS	LD50	3000	mg/kg
ORL	RAT	LD50	5800	mg/kg

ETHYL ACETATE

ORL	MUS	LD50	4100	mg/kg
ORL	RAT	LD50	5620	mg/kg
SCU	RAT	LDLO	5	gm/kg

LOW BOILING POINT NAPHTHA - UNSPECIFIED - SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM.

ORL	RAT	LD50	8400	mg/kg
-----	-----	------	------	-------

XYLENE

ORL	MUS	LD50	2119	mg/kg
ORL	RAT	LD50	4300	mg/kg
SCU	RAT	LD50	1700	mg/kg

Relevant hazards for product:

Hazard	Route	Basis
Serious eye damage/irritation	OPT	Hazardous: calculated
Respiratory/skin sensitisation	DRM	Hazardous: calculated
STOT-single exposure	-	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

[cont...]

SAFETY DATA SHEET
BODY COATING BLACK 500 ML

Page: 8

Other information: May cause drowsiness or dizziness.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values:

Species	Test	Value	Units
CAS 123-86-4	-	-	-
DAPHNIA	48H EC50	44	mg/l
ALGAE	96H EC50	320	mg/l
DAPHNIA	24H LC50	205	mg/l
CAS 141-78-6	-	-	-
DAPHNIA	24H EC50	2500	mg/l
CAS 64742-95-6	-	-	-
FISH	96H LC50	3,77	mg/l

Hazardous ingredients:

ACETONE

BLUEGILL (Lepomis macrochirus)	LC50	8300	mg/l
--------------------------------	------	------	------

12.2. Persistence and degradability

Persistence and degradability: No data available.

12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

12.4. Mobility in soil

Mobility: No data available.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Toxic to aquatic organisms. Water hazard class (NL) 8: Harmful to aquatic organisms; may cause long-term adverse effects in the aquatic environment. Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water. Danger to drinking water if even small quantities leak into the ground. Do not discharge into ground water, surface water or sewage system.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Must not be disposed together with household garbage or into the sewage system.

Waste code number: 08 01 11

[cont...]

SAFETY DATA SHEET
BODY COATING BLACK 500 ML

Page: 9

Disposal of packaging: Uncontaminated packaging can be recycled.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1950

14.2. UN proper shipping name

Shipping name: AEROSOLS

14.3. Transport hazard class(es)

Transport class: 2

14.4. Packing group

14.5. Environmental hazards

Environmentally hazardous: No

Marine pollutant: No

14.6. Special precautions for user

Special precautions: Warning: Gases. EMS number: F-D, S-U.

Tunnel code: D

Transport category: 2

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 2015/830.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: EUH066: Repeated exposure may cause skin dryness or cracking.

H220: Extremely flammable gas.

H222: Extremely flammable aerosol.

H225: Highly flammable liquid and vapour.

H226: Flammable liquid and vapour.

H229: Pressurised container: May burst if heated

[cont...]

SAFETY DATA SHEET
BODY COATING BLACK 500 ML

Page: 10

H304: May be fatal if swallowed and enters airways.

H312: Harmful in contact with skin.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H332: Harmful if inhaled.

H335: May cause respiratory irritation.

H336: May cause drowsiness or dizziness.

H411: Toxic to aquatic life with long lasting effects.

H412: Harmful to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.