

SAFETY DATA SHEET

HS EASY CLEAR

Page: 1

Compilation date: 09-05-2017

Revision No: 1

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: HS EASY CLEAR

Product code: 5801 / 5807

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: Uses in Coatings: Clear Coat

1.3. Details of the supplier of the safety data sheet

Company name: ProPart International B.V.

Molenakker 3

Reuver

5953 TW

The Netherlands

Tel: +31 (0) 77 476 2368

Fax: +31 (0) 77 476 2424

Email: info@propart-international.com

1.4. Emergency telephone number

Emergency tel: +31 (0) 77 476 2368 (08.30-17.00)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Flam. Liq. 3: H226; Asp. Tox. 1: H304; Aquatic Chronic 2: H411; Skin Irrit. 2: H315; STOT SE 3: H335; STOT SE 3: H336; -: EUH208

Most important adverse effects: Causes skin irritation. May cause respiratory irritation. Toxic to aquatic life with long lasting effects. Flammable liquid and vapour. May be fatal if swallowed and enters airways. May cause drowsiness or dizziness. Contains Bis 1,2,2,6,6-pentamethyl-4-piperidil) sebacate and methyl 1,2,2,6,6-pentamethyl-1,4-piperidil sebacate. May produce an allergic reaction.

2.2. Label elements

Label elements:

Hazard statements: H315: Causes skin irritation.

H335: May cause respiratory irritation.

H411: Toxic to aquatic life with long lasting effects.

H226: Flammable liquid and vapour.

H304: May be fatal if swallowed and enters airways.

H336: May cause drowsiness or dizziness.

SAFETY DATA SHEET

HS EASY CLEAR

Page: 2

EUH208: Contains Bis 1,2,2,6,6-pentamethyl-4-piperidil) sebacate and methyl 1,2,2,6,6-pentamethyl-1,4-piperidil sebacate. May produce an allergic reaction.

Hazard pictograms: GHS07: Exclamation mark

GHS09: Environmental

GHS02: Flame



Signal words: Danger

Precautionary statements: P280: Wear protective gloves/protective clothing/eye protection/face protection.

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P261: Avoid breathing dust/fumes/gas/mist/vapours/spray.

P273: Avoid release to the environment.

P301+310: IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P331: Do NOT induce vomiting.

P403+233: Store in a well-ventilated place. Keep container tightly closed.

P501: Dispose of contents/container to approved waste disposal according to local/regional/national/international regulations.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

LOW BOILING POINT NAPHTHA - UNSPECIFIED - SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM.

EINECS	CAS	PBT / WEL	CLP Classification	Percent
265-199-0	64742-95-6	-	Asp. Tox. 1: H304; Flam. Liq. 3: H226; STOT SE 3: H335; Aquatic Chronic 2: H411	30-50%

XYLENE

215-535-7	1330-20-7	-	Flam. Liq. 3: H226; Acute Tox. 4: H332; Acute Tox. 4: H312; Skin Irrit. 2: H315	10-30%
-----------	-----------	---	---	--------

N-BUTYL ACETATE

204-658-1	123-86-4	-	Flam. Liq. 3: H226; STOT SE 3: H336; -: EUH066	10-30%
-----------	----------	---	--	--------

Section 4: First aid measures

[cont...]

SAFETY DATA SHEET

HS EASY CLEAR

Page: 3

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water. Use an approved skin cleanser.

Eye contact: Remove contact lenses. Ensure adequate flushing of eyes by separating eyelids with the fingers. Consult a doctor.

Ingestion: Call a doctor immediately. Do not induce vomiting.

Inhalation: Provide fresh air. Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: Absorption through the skin may occur causing symptoms similar to those of inhalation. Repeated or prolonged contact with the preparation may result in removal of the natural fat of the skin, resulting in non-allergic skin inflammation and absorption through the skin.

Eye contact: There may be irritation and redness. The eyes may water profusely. When fluid spills into the eyes, this can cause irritation and recoverable damage.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: Exposure to decomposition products may cause a health hazard. Exposure to occupational exposure may have adverse effects on health: Irritation of mucous membranes and respiratory system, as well as adverse effects on kidneys, liver and central nervous system. Exposure may cause coughing or wheezing. Drowsiness or mental confusion may occur. In extreme cases, unconsciousness.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Never make an unconscious person anything by mouth. In case of doubt or in case of persistent symptoms, call for medical attention. Treat symptomatically.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Alcohol resistant foam. Do not use water. Sand or earth. CO2 Extinguishing powder.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes. Keep away from sources of ignition May contain carbon monoxide, carbon dioxide, nitrogen oxides.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

[cont...]

SAFETY DATA SHEET

HS EASY CLEAR

Page: 4

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Eliminate all sources of ignition. Ensure adequate ventilation. Do not breathe vapor.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS. See section 7 for information on safe handling

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air. Workers should wash hands and face before eating, drinking and smoking. Operators should wear antistatic footwear and clothing and floors should be of the conducting type. Do not eat, drink or smoke when using this product. Avoid breathing vapours or mist. Keep ignition sources away. Inhalation of abrasive must be avoided. Protect against electrostatic charges. Keep away from heat, sparks and flames. To eliminate static electricity during transport, the vessel must be earthed and connected to the receptacle using a tie strap. Without adequate ventilation, vapours may accumulate at ground level and, if ignited catch fire even at a distance, with the danger of backfire. If employees, even if they are not in the process of processing the product, are in a spray booth, ventilation should be present for any spray particles and solvent vapors. In these circumstances, they must wear a hood during the spraying process until the concentration has dropped below the MAC value.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed. Do not eat, drink or smoke when using this product. Keep away from sources of ignition. Do not use pressure when emptying. Is not a pressure vessel. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Keep only in original container. Keep away from: oxidising agents, strong alkalis, strong acids.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): No data available.

[cont...]

SAFETY DATA SHEET

HS EASY CLEAR

Page: 5

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

XYLENE

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	220 mg/m ³	441 mg/m ³	-	-

N-BUTYL ACETATE

UK	724 mg/m ³	966 mg/m ³	-	-
----	-----------------------	-----------------------	---	---

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. Where possible, this must be achieved through the use of local air outlet and good general suction capacity. If these are insufficient to maintain concentrations of particulate matter and vapors of solvents below the batch exposure limit, a suitable respiratory protective device should be worn.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Dry sanding of a paint coating, or machining with burners and/or welding equipment of coated objects can cause harmful dust and/or vapors. If possible, wet sanding should be preferred.

Hand protection: Protective gloves. Nitrile gloves. Protective creams can help protect exposed skin. However, these may not be applied after exposure has occurred.

Eye protection: Use eye protection (EN166) against splashing of liquids. Ensure eye bath is to hand.

Skin protection: Protective clothing. Workers should wear anti-static clothing of a natural material or of a heat-resistant synthetic material.

Environmental: Do not let away in sewers or water courses. See also sections 7 and 12.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Colourless

Odour: Characteristic odour

Solubility in water: Not miscible

Flash point°C: >+23

Relative density: 0.95 +/- 0.05 20°C

[cont...]

SAFETY DATA SHEET

HS EASY CLEAR

Page: 6

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.
Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: Can be released in case of fire: Carbon monoxide. Carbon dioxide (CO₂). Nitrogen oxides (NO_x).

Section 11: Toxicological information

11.1. Information on toxicological effects

Toxicity values:

Route	Species	Test	Value	Units
DERMAL	RBT	LD50	>4350	mg/kg
ORAL	RAT	LD50	4300	mg/kg

Hazardous ingredients:

LOW BOILING POINT NAPHTHA - UNSPECIFIED - SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM.

ORL	RAT	LD50	8400	mg/kg
-----	-----	------	------	-------

XYLENE

ORL	MUS	LD50	2119	mg/kg
ORL	RAT	LD50	4300	mg/kg
SCU	RAT	LD50	1700	mg/kg

[cont...]

SAFETY DATA SHEET

HS EASY CLEAR

Page: 7

N-BUTYL ACETATE

ORL	MUS	LD50	6	gm/kg
ORL	RAT	LD50	10768	mg/kg

Relevant hazards for product:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
STOT-single exposure	INH	Hazardous: calculated
Aspiration hazard	-	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: Absorption through the skin may occur causing symptoms similar to those of inhalation. Repeated or prolonged contact with the preparation may result in removal of the natural fat of the skin, resulting in non-allergic skin inflammation and absorption through the skin.

Eye contact: There may be irritation and redness. The eyes may water profusely. When fluid spills into the eyes, this can cause irritation and recoverable damage.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: Exposure to decomposition products may cause a health hazard. Exposure to occupational exposure may have adverse effects on health: Irritation of mucous membranes and respiratory system, as well as adverse effects on kidneys, liver and central nervous system. Exposure may cause coughing or wheezing. Drowsiness or mental confusion may occur. In extreme cases, unconsciousness.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values:

Species	Test	Value	Units
Daphnia magna	24H EC50	150	mg/l

12.2. Persistence and degradability

Persistence and degradability: No data available.

12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

[cont...]

SAFETY DATA SHEET

HS EASY CLEAR

Page: 8

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Toxic to aquatic organisms. Toxic to soil organisms.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company. Do not discharge into sewers or drains. The classification of the product may match the criteria for hazardous waste.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1263

14.2. UN proper shipping name

Shipping name: PAINT

14.3. Transport hazard class(es)

Transport class: 3

14.4. Packing group

Packing group: III

14.5. Environmental hazards

Environmentally hazardous: Yes

Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: D/E

Transport category: 3

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

[cont...]

SAFETY DATA SHEET

HS EASY CLEAR

Page: 9

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 2015/830.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: EUH066: Repeated exposure may cause skin dryness or cracking.

EUH208: Contains <name of sensitising substance>. May produce an allergic reaction.

H226: Flammable liquid and vapour.

H304: May be fatal if swallowed and enters airways.

H312: Harmful in contact with skin.

H315: Causes skin irritation.

H332: Harmful if inhaled.

H335: May cause respiratory irritation.

H336: May cause drowsiness or dizziness.

H411: Toxic to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.

