

**SAFETY DATA SHEET**

HS EASY FILLER

Page: 1

Compilation date: 23-05-2017

Revision No: 1

**Section 1: Identification of the substance/mixture and of the company/undertaking**

**1.1. Product identifier**

**Product name:** HS EASY FILLER

**Product code:** 5830

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

**Use of substance / mixture:** Use in coatings: Primer / Filler

**1.3. Details of the supplier of the safety data sheet**

**Company name:** ProPart International B.V.

Molenakker 3

Reuver

5953 TW

The Netherlands

**Tel:** +31 (0) 77 476 2368

**Fax:** +31 (0) 77 476 2424

**Email:** [info@propart-international.com](mailto:info@propart-international.com)

**1.4. Emergency telephone number**

**Emergency tel:** +31 (0) 77 476 2368 (08.30-17.00)

**Section 2: Hazards identification**

**2.1. Classification of the substance or mixture**

**Classification under CLP:** Asp. Tox. 1: H304; Aquatic Chronic 3: H412; Flam. Liq. 3: H226

**Most important adverse effects:** Flammable liquid and vapour. May be fatal if swallowed and enters airways. Harmful to aquatic life with long lasting effects.

**2.2. Label elements**

**Label elements:**

**Hazard statements:** H226: Flammable liquid and vapour.

H304: May be fatal if swallowed and enters airways.

H412: Harmful to aquatic life with long lasting effects.

**Hazard pictograms:** GHS02: Flame

GHS08: Health hazard



**Signal words:** Warning

**Precautionary statements:** P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition

# SAFETY DATA SHEET

HS EASY FILLER

Page: 2

sources. No smoking.

P301+310: IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P501: Dispose of contents/container to hazardous or special waste collection point.

## 2.3. Other hazards

**PBT:** This product is not identified as a PBT/vPvB substance.

## Section 3: Composition/information on ingredients

### 3.2. Mixtures

#### Hazardous ingredients:

LOW BOILING POINT NAPHTHA - UNSPECIFIED - NATURAL GAS CONDENSATES

EINECS	CAS	PBT / WEL	CLP Classification	Percent
272-896-3	68919-39-1	-	Asp. Tox. 1: H304; Skin Irrit. 2: H315; Aquatic Chronic 2: H411	6.500%

XYLENE

215-535-7	1330-20-7	-	Flam. Liq. 3: H226; Acute Tox. 4: H332; Acute Tox. 4: H312; Skin Irrit. 2: H315	4.500%
-----------	-----------	---	--	--------

N-BUTYL ACETATE

204-658-1	123-86-4	-	Flam. Liq. 3: H226; STOT SE 3: H336; -: EUH066	3.000%
-----------	----------	---	---	--------

## Section 4: First aid measures

### 4.1. Description of first aid measures

**Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.

**Eye contact:** Remove contact lenses. Ensure adequate flushing of eyes by separating eyelids with the fingers. Consult a doctor.

**Ingestion:** Do not induce vomiting. Call a doctor immediately.

**Inhalation:** Provide fresh air. See a doctor immediately.

### 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be irritation and redness at the site of contact. Symptoms and symptoms include headache, dizziness, fatigue, muscle weakness, drowsiness and in extreme cases unconsciousness. Repeated or prolonged contact with the preparation may result in removal of the natural fat of the skin, resulting in non-allergic skin inflammation and absorption through the skin.

**Eye contact:** When fluid spills into the eyes, this can cause irritation and recoverable damage.

**Ingestion:** There may be soreness and redness of the mouth and throat.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest. Exposure to occupational exposure may have adverse effects on health: Irritation of mucous

[cont...]

# SAFETY DATA SHEET

HS EASY FILLER

Page: 3

membranes and respiratory system, as well as adverse effects on kidneys, liver and central nervous system.

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

## 4.3. Indication of any immediate medical attention and special treatment needed

**Immediate / special treatment:** Never give anything by mouth to an unconscious person. In case of doubt or in case of persistent symptoms, call for medical attention. Treat symptomatically. See section 11

## Section 5: Fire-fighting measures

### 5.1. Extinguishing media

**Extinguishing media:** Suitable extinguishing media for the surrounding fire should be used. Alcohol resistant foam. Sand or earth. CO2 Do not use water.

### 5.2. Special hazards arising from the substance or mixture

**Exposure hazards:** May contain carbon monoxide, carbon dioxide, nitrogen oxides. Can form explosive vapor-air mixtures Keep away from sources of ignition

### 5.3. Advice for fire-fighters

**Advice for fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

## Section 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions:** Turn leaking containers leak-side up to prevent the escape of liquid. Keep away from ignition sources Ensure adequate ventilation. Do not breathe vapor.

### 6.2. Environmental precautions

**Environmental precautions:** Do not discharge into drains or rivers. Contain the spillage using bunding. Notify authorities if product enters sewers or public waters.

### 6.3. Methods and material for containment and cleaning up

**Clean-up procedures:** Absorb into dry earth or sand. Mix with sand or vermiculite. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

### 6.4. Reference to other sections

**Reference to other sections:** Refer to section 8 of SDS. See section 7 for information on safe handling Refer to section 13 of SDS.

## Section 7: Handling and storage

### 7.1. Precautions for safe handling

**Handling requirements:** Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air. Do not eat, drink or smoke when using this product. Wash hands before breaks and at the

[cont...]

# SAFETY DATA SHEET

HS EASY FILLER

Page: 4

end of workday. Workers should wash hands and face before eating, drinking and smoking. Keep away from heat, sparks and flames. To eliminate static electricity during transport, the vessel must be earthed and connected to the receptacle using a tie strap. If employees, even if they are not in the process of processing the product, are in a spray booth, ventilation should be present for any spray particles and solvent vapors. In these circumstances, they must wear a hood during the spraying process until the concentration has dropped below the MAC value. Vapors are heavier than air and can spread over floors. Vapors may form an explosive mixture with air.

## 7.2. Conditions for safe storage, including any incompatibilities

**Storage conditions:** Store in a cool, well ventilated area. Keep container tightly closed. Keep away from sources of ignition. Do not use pressure when emptying. Is not a pressure vessel. Keep away from alkalis, oxidizing substances, acids. Do not throw waste in the sink. Keep only in original container. Keep the product in containers clearly labeled. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

## 7.3. Specific end use(s)

**Specific end use(s):** No data available.

## Section 8: Exposure controls/personal protection

### 8.1. Control parameters

**Hazardous ingredients:**

**XYLENE**

**Workplace exposure limits:**

**Respirable dust**

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	220 mg/m <sup>3</sup>	441 mg/m <sup>3</sup>	-	-

**N-BUTYL ACETATE**

UK	724 mg/m <sup>3</sup>	966 mg/m <sup>3</sup>	-	-
----	-----------------------	-----------------------	---	---

### DNEL/PNEC Values

**DNEL / PNEC** No data available.

### 8.2. Exposure controls

**Engineering measures:** Ensure there is sufficient ventilation of the area. Where possible, this must be achieved through the use of local air outlet and good general suction capacity. If these are insufficient to maintain concentrations of particulate matter and vapors of solvents below the batch exposure limit, a suitable respiratory protective device should be worn.

**Respiratory protection:** Self-contained breathing apparatus must be available in case of emergency. In case of intensive or longer exposure or low pollution use self-contained respiratory protective device. Dry sanding of a paint coating, or machining with burners and/or welding

[cont...]

# SAFETY DATA SHEET

HS EASY FILLER

Page: 5

equipment of coated objects can cause harmful dust and/or vapors. If possible, wet sanding should be preferred.

**Hand protection:** Protective gloves. Use suitable gloves (EN375) for prolonged or repeated use. Type: Nitrile.

**Eye protection:** Use eye protection (EN166) against splashing of liquids. Ensure eye bath is to hand.

**Skin protection:** Protective clothing. Workers should wear anti-static clothing of a natural material or of a heat-resistant synthetic material.

**Environmental:** Do not let away in sewers or water courses. See also sections 7 and 12.

## Section 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

**State:** Liquid

**Colour:** Volgens de productbeschrijving.

**Odour:** Characteristic odour

**Solubility in water:** Insoluble

**Viscosity:** 14 +/- 1

**Flash point°C:** >+23

**Relative density:** 1,6 +/- 0.05 (20°C)

### 9.2. Other information

**Other information:** No data available.

## Section 10: Stability and reactivity

### 10.1. Reactivity

**Reactivity:** Stable under recommended transport or storage conditions.

### 10.2. Chemical stability

**Chemical stability:** Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

**Hazardous reactions:** Hazardous reactions will not occur under normal transport or storage conditions. Decomposition may occur on exposure to conditions or materials listed below.

### 10.4. Conditions to avoid

**Conditions to avoid:** Heat. Any contact with oxidizing agents, strong bases and strong acids should be avoided.

### 10.5. Incompatible materials

**Materials to avoid:** Strong oxidising agents. Strong acids.

### 10.6. Hazardous decomposition products

**Haz. decomp. products:** In combustion emits toxic fumes. Can be released in case of fire: Carbon monoxide. Carbon dioxide (CO<sub>2</sub>). Nitrogen oxides (NO<sub>x</sub>).

[cont...]

# SAFETY DATA SHEET

HS EASY FILLER

Page: 6

## Section 11: Toxicological information

### 11.1. Information on toxicological effects

#### Toxicity values:

Route	Species	Test	Value	Units
1330-20-7	-	-	-	-
DERMAL	RBT	LD50	>4350	mg/kg
ORAL	RAT	LD50	4300	mg/kg
123-86-4	-	-	-	-
DERMAL	RBT	LD50	141400	mg/kg
ORAL	RAT	LD50	13100	mg/kg
64742-95-6	-	-	-	-
DERMAL	RBT	LD50	>20000	mg/kg
ORAL	RAT	LD50	>3500	mg/kg

#### Hazardous ingredients:

##### XYLENE

ORL	MUS	LD50	2119	mg/kg
ORL	RAT	LD50	4300	mg/kg
SCU	RAT	LD50	1700	mg/kg

##### N-BUTYL ACETATE

ORL	MUS	LD50	6	gm/kg
ORL	RAT	LD50	10768	mg/kg

#### Relevant hazards for product:

Hazard	Route	Basis
Aspiration hazard	-	Hazardous: calculated

### Symptoms / routes of exposure

**Skin contact:** There may be irritation and redness at the site of contact. Symptoms and symptoms include headache, dizziness, fatigue, muscle weakness, drowsiness and in extreme cases unconsciousness. Repeated or prolonged contact with the preparation may result in removal of the natural fat of the skin, resulting in non-allergic skin inflammation and absorption through the skin.

**Eye contact:** When fluid spills into the eyes, this can cause irritation and recoverable damage.

**Ingestion:** There may be soreness and redness of the mouth and throat.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest. Exposure to occupational exposure may have adverse effects on health: Irritation of mucous membranes and respiratory system, as well as adverse effects on kidneys, liver and central nervous system.

[cont...]

# SAFETY DATA SHEET

HS EASY FILLER

Page: 7

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

## Section 12: Ecological information

### 12.1. Toxicity

#### Ecotoxicity values:

Species	Test	Value	Units
CAS 1330-20-7	-	-	-
Daphnia magna	24H EC50	150	mg/l
CAS 123-86-4	-	-	-
Daphnia magna	24H EC50	73	mg/l
CAS64742-95-6	-	-	-
Daphnia magna	24H EC50	170	mg/l

### 12.2. Persistence and degradability

**Persistence and degradability:** No data available.

### 12.3. Bioaccumulative potential

**Bioaccumulative potential:** No data available.

### 12.4. Mobility in soil

**Mobility:** No data available.

### 12.5. Results of PBT and vPvB assessment

**PBT identification:** This product is not identified as a PBT/vPvB substance.

### 12.6. Other adverse effects

**Other adverse effects:** No data available.

## Section 13: Disposal considerations

### 13.1. Waste treatment methods

**Disposal operations:** Recommendation: Disposal must be made according to official regulations. Do not discharge into sewers or drains. The classification of the product may meet the criteria for a hazardous waste.

**Recovery operations:** Disposal must be made according to official regulations.

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

## Section 14: Transport information

### 14.1. UN number

**UN number:** UN1263

[cont...]

# SAFETY DATA SHEET

HS EASY FILLER

Page: 8

## 14.2. UN proper shipping name

Shipping name: PAINT

## 14.3. Transport hazard class(es)

Transport class: 3

## 14.4. Packing group

Packing group: III

## 14.5. Environmental hazards

Environmentally hazardous: No

Marine pollutant: No

## 14.6. Special precautions for user

Special precautions: See section 6-8.

Tunnel code: D/E

Transport category: 3

## Section 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

**Specific regulations:** Not applicable. The product is classified and labeled for delivery in accordance with Directive 1999/45 / EC. The Safety Data Sheet has been prepared in accordance with EU Regulation (EC) No. 1907/2006 (REACH). In accordance with EU Directive 2004/42 / EC: 2004/42 / IIB (c) (540) 480.

### 15.2. Chemical Safety Assessment

**Chemical safety assessment:** A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

## Section 16: Other information

### Other information

**Other information:** This safety data sheet is prepared in accordance with Commission Regulation (EU) No 2015/830.

\* indicates text in the SDS which has changed since the last revision.

**Phrases used in s.2 and s.3:** EUH066: Repeated exposure may cause skin dryness or cracking.

H226: Flammable liquid and vapour.

H304: May be fatal if swallowed and enters airways.

H312: Harmful in contact with skin.

H315: Causes skin irritation.

H332: Harmful if inhaled.

H336: May cause drowsiness or dizziness.

H411: Toxic to aquatic life with long lasting effects.

H412: Harmful to aquatic life with long lasting effects.

[cont...]



## **SAFETY DATA SHEET**

HS EASY FILLER

**Page:** 9

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.

