

SAFETY DATA SHEET

ACRYLIC THINNER

Page: 1

Compilation date: 26-06-2017

Revision No: 1

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: ACRYLIC THINNER

Product code: 5870-5871

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: Use in coatings: Dilution

1.3. Details of the supplier of the safety data sheet

Company name: ProPart International B.V.

Molenakker 3

Reuver

5953 TW

The Netherlands

Tel: +31 (0) 77 476 2368

Fax: +31 (0) 77 476 2424

Email: info@propart-international.com

1.4. Emergency telephone number

Emergency tel: +31 (0) 77 476 2368 (08.30-17.00)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Flam. Liq. 3: H226; Aquatic Chronic 3: H412; Skin Irrit. 2: H315; STOT SE 3: H336; Asp. Tox. 1: H304

Most important adverse effects: Flammable liquid and vapour. May be fatal if swallowed and enters airways. Causes skin irritation. May cause drowsiness or dizziness. Harmful to aquatic life with long lasting effects.

2.2. Label elements

Label elements:

Hazard statements: H226: Flammable liquid and vapour.

H304: May be fatal if swallowed and enters airways.

H315: Causes skin irritation.

H336: May cause drowsiness or dizziness.

H412: Harmful to aquatic life with long lasting effects.

Hazard pictograms: GHS02: Flame

GHS08: Health hazard



[cont...]

SAFETY DATA SHEET

ACRYLIC THINNER

Page: 2

Signal words: Danger

Precautionary statements: P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261: Avoid breathing dust/fumes/gas/mist/vapours/spray.
P280: Wear protective gloves/protective clothing/eye protection/face protection.
P301+310: IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P331: Do NOT induce vomiting.
P501: Dispose of contents/container to hazardous or special waste collection point.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

N-BUTYL ACETATE

EINECS	CAS	PBT / WEL	CLP Classification	Percent
204-658-1	123-86-4	-	Flam. Liq. 3: H226; STOT SE 3: H336; -: EUH066	40.000%

XYLENE

215-535-7	1330-20-7	-	Flam. Liq. 3: H226; Acute Tox. 4: H332; Acute Tox. 4: H312; Skin Irrit. 2: H315	35.000%
-----------	-----------	---	--	---------

LOW BOILING POINT NAPHTHA - UNSPECIFIED - SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM.

265-199-0	64742-95-6	-	Asp. Tox. 1: H304; Flam. Liq. 3: H226; STOT SE 3: H335; Aquatic Chronic 2: H411	5.000%
-----------	------------	---	---	--------

2-METHOXY-1-METHYLETHYL ACETATE

203-603-9	108-65-6	Substance with a Community workplace exposure limit.	Flam. Liq. 3: H226	5.000%
-----------	----------	---	--------------------	--------

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water. Use an approved skin cleanser.

Eye contact: Remove contact lenses. Ensure adequate flushing of eyes by separating eyelids with the fingers. Consult a doctor.

Ingestion: Immediately call a POISON CENTER or physician. Do not induce vomiting. May be fatal if the substance gets into the respiratory tract if swallowed.

Inhalation: Provide fresh air. In case of complaints consult doctor.

[cont...]

SAFETY DATA SHEET

ACRYLIC THINNER

Page: 3

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: Symptoms and symptoms include headache, dizziness, fatigue, muscle weakness, drowsiness and in extreme cases unconsciousness. Repeated or prolonged contact with the preparation may result in removal of the natural fat of the skin, resulting in non-allergic skin inflammation and absorption through the skin.

Eye contact: When fluid spills into the eyes, this can cause irritation and recoverable damage.

Ingestion: In case of swallowing consult a doctor immediately. May be deadly if the substance gets into the airways if swallowed.

Inhalation: Exposure to occupational exposure may have adverse effects on health: Irritation of mucous membranes and respiratory system, as well as adverse effects on kidneys, liver and central nervous system. Symptoms may include irritation of mucous membranes and respiratory tract, as well as adverse effects on kidneys, liver and central nervous system. May be fatal if the substance gets into the airways if swallowed.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: In case of doubt or in case of persistent symptoms, call for medical attention. Never give anything by mouth to an unconscious person. Treat symptomatically. Eye bathing equipment should be available on the premises.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Alcohol resistant foam. CO2 powders. Sand or earth. Do not use water.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: May contain carbon monoxide, carbon dioxide, nitrogen oxides. Forms explosive air-vapour mixture.

5.3. Advice for fire-fighters

Advice for fire-fighters: Vapor in the air can form an explosive mixture with air. Remove all ignition sources. Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Eliminate all sources of ignition. Ensure adequate ventilation. Turn leaking containers leak-side up to prevent the escape of liquid. Refer to section 8 of SDS for personal protection details.

6.2. Environmental precautions

Environmental precautions: Notify authorities if product enters sewers or public waters. Do not discharge into drains or rivers.

[cont...]

SAFETY DATA SHEET

ACRYLIC THINNER

Page: 4

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Collect spillage with non-combustible absorbent material such as sand, earth, vermiculite and dispose of it in a waste container in accordance with local regulations (see section 13).

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS. See section 7 for information on safe handling

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid the formation or spread of mists in the air. Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Smoking is forbidden. Use non-sparking tools. Eating, drinking, smoking and storing food is prohibited in workspace. Not breathe vapors / dust. Workers should wash hands and face before eating, drinking and smoking. To eliminate static electricity during transport, the vessel must be earthed and connected to the receptacle using a tie strap. If employees, even if they are not in the process of processing the product, are in a spray booth, ventilation should be present for any spray particles and solvent vapors. In these circumstances, they must wear a hood during the spraying process until the concentration has dropped below the MAC value. Vapors are heavier than air and can spread over floors. Vapors may form an explosive mixture with air. Prevent the formation of flammable or explosive concentrations of vapors in the air. Protect against electrostatic charges.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed. Keep away from sources of ignition. Do not use pressure when emptying. Is not a pressure vessel. Keep only in original container. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not throw waste in the sink. Keep away from: oxidising agents, strong alkalis, strong acids.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

[cont...]

SAFETY DATA SHEET

ACRYLIC THINNER

Page: 5

N-BUTYL ACETATE

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	724 mg/m ³	966 mg/m ³	-	-

XYLENE

UK	220 mg/m ³	441 mg/m ³	-	-
----	-----------------------	-----------------------	---	---

2-METHOXY-1-METHYLETHYL ACETATE

UK	274 mg/m ³	548 mg/m ³	-	-
----	-----------------------	-----------------------	---	---

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. Ensure lighting and electrical equipment are not a source of ignition. Where possible, this must be achieved through the use of local air outlet and good general suction capacity. If these are insufficient to maintain concentrations of particulate matter and vapors of solvents below the batch exposure limit, a suitable respiratory protective device should be worn.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Dry sanding of a paint coating, or machining with burners and/or welding equipment of coated objects can cause harmful dust and/or vapors. If possible, wet sanding should be preferred.

Hand protection: Use suitable gloves (EN375) for prolonged or repeated use. Type: Nitrile. Protective creams can help protect exposed skin. However, these may not be applied after exposure has occurred.

Eye protection: Use eye protection (EN166) against splashing of liquids. Ensure eye bath is to hand.

Skin protection: Workers should wear anti-static clothing of a natural material or of a heat-resistant synthetic material.

Environmental: Do not let away in sewers or water courses. See also sections 7 and 12.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Transparent.

Odour: Characteristic odour

Solubility in water: Insoluble

Flash point°C: >+23

Relative density: 0,88 +/- 0,03 (20°C)

[cont...]

SAFETY DATA SHEET

ACRYLIC THINNER

Page: 6

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions. Stable at room temperature.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat. Hot surfaces. Sources of ignition. Flames.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes. Carbon monoxide, carbon dioxide and nitrogen oxides.

Section 11: Toxicological information

11.1. Information on toxicological effects

Toxicity values:

Route	Species	Test	Value	Units
1330-20-7	-	-	-	-
DERMAL	RBT	LD50	>4350	mg/kg
ORAL	RAT	LD50	4300	mg/kg
123-86-4	-	-	-	-
DERMAL	RBT	LD50	141400	mg/kg
ORAL	RAT	LD50	13100	mg/kg
64742-95-6	-	-	-	-
DERMAL	RBT	LD50	>20000	mg/kg
108-65-6	-	-	-	-
ORAL	RAT	LD50	>10000	mg/kg

[cont...]

SAFETY DATA SHEET

ACRYLIC THINNER

Page: 7

Hazardous ingredients:

N-BUTYL ACETATE

ORL	MUS	LD50	6	gm/kg
ORL	RAT	LD50	10768	mg/kg

XYLENE

ORL	MUS	LD50	2119	mg/kg
ORL	RAT	LD50	4300	mg/kg
SCU	RAT	LD50	1700	mg/kg

LOW BOILING POINT NAPHTHA - UNSPECIFIED - SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM.

ORL	RAT	LD50	8400	mg/kg
-----	-----	------	------	-------

2-METHOXY-1-METHYLETHYL ACETATE

IPR	MUS	LD50	750	mg/kg
ORL	RAT	LD50	8532	mg/kg

Relevant hazards for product:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
STOT-single exposure	-	Hazardous: calculated
Aspiration hazard	-	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: Symptoms and symptoms include headache, dizziness, fatigue, muscle weakness, drowsiness and in extreme cases unconsciousness. Repeated or prolonged contact with the preparation may result in removal of the natural fat of the skin, resulting in non-allergic skin inflammation and absorption through the skin.

Eye contact: When fluid spills into the eyes, this can cause irritation and recoverable damage.

Ingestion: In case of swallowing consult a doctor immediately. May be deadly if the substance gets into the airways if swallowed.

Inhalation: Exposure to occupational exposure may have adverse effects on health: Irritation of mucous membranes and respiratory system, as well as adverse effects on kidneys, liver and central nervous system. Symptoms may include irritation of mucous membranes and respiratory tract, as well as adverse effects on kidneys, liver and central nervous system. May be fatal if the substance gets into the airways if swallowed.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

[cont...]

SAFETY DATA SHEET

ACRYLIC THINNER

Page: 8

12.1. Toxicity

Ecotoxicity values:

Species	Test	Value	Units
CAS 1330-20-7	-	-	-
Daphnia magna	24H EC50	150	mg/l
CAS 123-86-4	-	-	-
Daphnia magna	24H EC50	73	mg/l
CAS 64742-95-6	-	-	-
Daphnia magna	24H EC50	170	mg/l
CAS 108-65-6	-	-	-
Daphnia magna	48H EC50	>500	mg/l

12.2. Persistence and degradability

Persistence and degradability: No data available.

12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

12.4. Mobility in soil

Mobility: No data available.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: No data available.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Possible restrictive regulations by local authority should always be adhered to. Transfer to a suitable container and arrange for collection by specialised disposal company. The classification of the product may meet the criteria for a hazardous waste. Do not let away in sewers or water courses.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1263

[cont...]

SAFETY DATA SHEET

ACRYLIC THINNER

Page: 9

14.2. UN proper shipping name

Shipping name: PAINT

14.3. Transport hazard class(es)

Transport class: 3

14.4. Packing group

Packing group: III

14.5. Environmental hazards

Environmentally hazardous: No

Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: D/E

Transport category: 3

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: The product is classified and labeled for delivery in accordance with Directive 1999/45 / EC. The Safety Data Sheet has been prepared in accordance with EU Regulation (EC) No. 1907/2006 (REACH).

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 2015/830.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: EUH066: Repeated exposure may cause skin dryness or cracking.

H226: Flammable liquid and vapour.

H304: May be fatal if swallowed and enters airways.

H312: Harmful in contact with skin.

H315: Causes skin irritation.

H332: Harmful if inhaled.

H335: May cause respiratory irritation.

H336: May cause drowsiness or dizziness.

H411: Toxic to aquatic life with long lasting effects.

H412: Harmful to aquatic life with long lasting effects.

[cont...]

SAFETY DATA SHEET

ACRYLIC THINNER

Page: 10

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.

