

CHEMICAL ANCHOR ETA APPR.

Page: 1

Compilation date: 19-03-2014

Revision No: 1

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: CHEMICAL ANCHOR ETA APPR.

Product code: 7110

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC1: Adhesives, sealants.

1.3. Details of the supplier of the safety data sheet

Company name: ProPart International B.V.

Molenakker 3

Reuver 5953 TW

The Netherlands

Tel: +31 (0) 77 476 2368 **Fax:** +31 (0) 77 476 2424

Email: info@propart-international.com

1.4. Emergency telephone number

Emergency tel: +31 (0) 77 476 2368 (08.30-17.00)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CHIP: O: R7; Xi: R36; Sens.: R43; -: R52/53

Classification under CLP: Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin Sens. 1: H317

Most important adverse effects: May cause fire. Irritating to eyes. May cause sensitisation by skin contact. Harmful to

aquatic organisms, may cause long-term adverse effects in the aquatic environment.

2.2. Label elements

Label elements under CLP:

Hazard statements: H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

Signal words: Warning

Hazard pictograms: GHS07: Exclamation mark



Precautionary statements: P264: Wash hands thoroughly after handling.

CHEMICAL ANCHOR ETA APPR.

Page: 2

P332+313: If skin irritation occurs: Get medical advice/attention.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P321: Specific treatment (see instruction on this label).

P362: Take off contaminated clothing and wash before reuse.

P261: Avoid breathing dust/fumes/gas/mist/vapours/spray.

P272: Contaminated work clothing should not be allowed out of the workplace.

P302+352: IF ON SKIN: Wash with plenty of soap and water.

P333+313: If skin irritation or rash occurs: Get medical advice/attention.

P337+313: If eye irritation persists: Get medical advice/attention.

P363: Wash contaminated clothing before reuse.

P501: Dispose of contents/container to waste according to

local/regional/national/international regulations.

Label elements under CHIP:

Hazard symbols: Irritant.



Risk phrases: R7: May cause fire.

R36: Irritating to eyes.

R43: May cause sensitisation by skin contact.

R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the

aquatic environment.

Safety phrases: S7: Keep container tightly closed.

S14: Keep away from reducing agents, oxidizing agents, acids, alkalis, amines, metals,

heavy-metal compounds.

S23: Do not breathe in.

S24/25: Avoid contact with skin and eyes.

S37: Wear suitable gloves.

S36/37/39: Wear suitable protective clothing, gloves and eye / face protection.

S51: Use only in well-ventilated areas.

2.3. Other hazards

PBT: This product is not identified as a PBT substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

CHEMICAL ANCHOR ETA APPR.

Page: 3

Hazardous ingredients:

BENZENE, ETHENYLMETHYL-

				_
EINECS	CAS	CHIP Classification	CLP Classification	Percent
246-562-2	25013-15-4	-: R10; Xi: R36/37/38; Sens.: R43	Flam. Liq. 3: H226; Eye Irrit. 2: H319;	6.250%
			Skin Irrit. 2: H315; Skin Sens. 1: H317	
2-HYDROXYE	THYL METHAC	RYLATE		
212-782-2	868-77-9	Xi: R36/38; Sens.: R43	Eye Irrit. 2: H319; Skin Irrit. 2: H315;	6.250%
			Skin Sens. 1: H317	
ETHYLENE DI	METHACRYLAT	Ē		
202-617-2	97-90-5	Xi: R37; Sens.: R43	STOT SE 3: H335; Skin Sens. 1: H317	3.000%
DIBENZOYL P	EROXIDE			
202-327-6	94-36-0	E: R3; O: R7; Xi: R36; Sens.: R43	Skin Sens. 1: H317; Org. Perox. B:	1.250%
			H241; Eye Irrit. 2: H319	
1,4-BUTANED	IOL DIMETHAC	RYLATE		
218-218-1	2082-81-7	Xi: R36/37/38; Sens.: R43	Skin Irrit. 2: H315; Eye Irrit. 2: H319;	1.250%
			Skin Sens. 1: H317; STOT SE 3: H335	
2-HYDROXYP	ROPYL METHA	CRYLATE		
213-090-3	923-26-2	Xi: R36; Sens.: R43	Eye Irrit. 2: H319; Skin Sens. 1: H317	1.250%
DIISOPROPAI	NOL-P-TOLUIDI	NE		
254-075-1	38668-48-3	T: R25; Xi: R36; -: R52/53	-	0.250%

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash

immediately with plenty of soap and water. Consult a doctor.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Consult a doctor. Do not induce vomiting.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. If

unconscious and breathing is OK, place in the recovery position. Move to fresh air in case of accidental inhalation of vapours. If unconscious, check for breathing and apply

artificial respiration if necessary. Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: Exposure may cause coughing or wheezing.

Delayed / immediate effects: Delayed effects can be expected after long-term exposure.

CHEMICAL ANCHOR ETA APPR.

Page: 4

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Show this safety data sheet to the doctor in attendance.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Dry chemical powder. Carbon dioxide. Alcohol resistant foam. Water spray. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes. In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Do not attempt to take action without suitable protective clothing - see section 8 of SDS.

Do not create dust. Eliminate all sources of ignition.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Transfer to a closable, labelled salvage container for disposal by an appropriate method. Absorb into dry earth or sand. Refer to section 13 of SDS for suitable method of disposal.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Avoid the formation or spread of dust in the air. Smoking is forbidden.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed. Keep away from sources of ignition. Prevent the build up of electrostatic charge in the immediate area.

CHEMICAL ANCHOR ETA APPR.

Page: 5

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

DIBENZOYL PEROXIDE

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	5 mg/m3	•	-	-

8.1. DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency. Respiratory

protective device with particle filter. Gas/vapour filter, type A: organic vapours (EN141).

Hand protection: Gloves resistant against chemicals (EN374). Do not use PVC gloves as PVC absorbs

acrylates.

Eye protection: Ensure eye bath is to hand. Safety glasses with side-shields.

Skin protection: Protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Paste Colour: Beige

Odour: Characteristic odour

Solubility in water: Not miscible

Viscosity: 22000 cps (20°C)

Kinematic viscosity: 4400 mm2/s

Boiling point/range°C: 171.9 Flammability limits %: lower: 0.8 Volume 25°C

upper: 11.0 Volume 25°C Flash point°C: 61

Autoflammability°C: 80 **Vapour pressure:** 0.88 kPa at 50°C

VOC g/I: 113.5

9.2. Other information

Other information: Vapour density: 1.1 at 20°C 1 atm. Relative air. Relative density: 1.75 at 20/4°C Relative

water.

CHEMICAL ANCHOR ETA APPR.

Page: 6

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat. Light. Humidity.

10.5. Incompatible materials

Materials to avoid: Reducing agents. Oxidising agents. Acids. Alkalis. Amines. Metals. Heavy-metal

compounds. Peroxides. Polymerization initiators.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

BENZENE, ETHENYLMETHYL-

ORAL RAT	LD50	2255	mg/kg
----------	------	------	-------

2-HYDROXYETHYL METHACRYLATE

IPR	RAT	LD50	1250	mg/kg
ORL	MUS	LD50	3275	mg/kg
ORL	RAT	LD50	5050	mg/kg

ETHYLENE DIMETHACRYLATE

IPR	RAT	LD50	2800	mg/kg
ORL	MUS	LD50	2	gm/kg
ORL	RAT	LD50	3300	mg/kg

DIBENZOYL PEROXIDE

OPI	MIIC	I DEO	F700	mallea
ORL	MUS	LD50	5700	mg/kg

CHEMICAL ANCHOR ETA APPR.

Page: 7

ORL	RAT	LD50	7710	ma/ka
0112	100			···g/···g

2-HYDROXYPROPYL METHACRYLATE

ORL	MUS	LD50	7964	ma/ka	
				3 3	

Relevant effects for mixture:

Effect	Route	Basis
Irritation	OPT	Hazardous: calculated
Sensitisation	DRM	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: Exposure may cause coughing or wheezing.

Delayed / immediate effects: Delayed effects can be expected after long-term exposure.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values:

Species	Test	Value	Units
FISH	96H LC50	227	mg/l
DAPHNIA	48H EC50	380	mg/l
ALGAE	72H EC50	836	mg/l

12.2. Persistence and degradability

Persistence and degradability: No data available.

12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

12.4. Mobility in soil

Mobility: No data available.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT substance.

12.6. Other adverse effects

Other adverse effects: No data available.

Section 13: Disposal considerations

CHEMICAL ANCHOR ETA APPR.

Page: 8

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal

company.

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

Section 14: Transport information

Transport class: This product does not require a classification for transport.

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture

by the supplier.

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

453/2010.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and 3: H226: Flammable liquid and vapour.

H241: Heating may cause a fire or explosion.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H335: May cause respiratory irritation.

R3: Extreme risk of explosion by shock, friction, fire or other sources of ignition.

R7: May cause fire.

R10: Flammable.

R25: Toxic if swallowed.

R36/37/38: Irritating to eyes, respiratory system and skin.

R36/38: Irritating to eyes and skin.

R36: Irritating to eyes.

R37: Irritating to respiratory system.

R43: May cause sensitisation by skin contact.

R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the

aquatic environment.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive

and shall be used only as a guide. This company shall not be held liable for any

damage resulting from handling or from contact with the above product.