

# FOOD GRADE GREASE

LUBRICATION AND MAINTENANCE

- **Very good adhesion**
- **High viscosity**
- **Contains PTFE (Polytetrafluoroethylene)**
- **Directed jet spray**

## PRODUCT DESCRIPTION :

High quality spray grease with PTFE for treatment of mechanical parts made of metal and plastics. Due the high viscosity, suitable for lubricating highly targeted parts, which are subjected to high pressure. The unique formula makes it suitable for use in the food industry.

Corresponding NSF registration H1.

- National Sanitation Foundation registration NSF-H1, number 149252
- Excellent mechanic land thermal stability
- Prevents wear and sticking
- Weather Resistance
- Resistant to weak acids and bases
- Excellent corrosion prevention
- Water resistant

## APPLICATIONS :

- Metal to metal connections
- Metal to plastic connections
- Hinges of doors
- Bearings
- Springs
- Stabilization rubbers
- Worm wheels
- Conveyors

## INSTRUCTIONS :

For use, read and follow the instructions on the package carefully. Bring the Aerosol to room temperature. Ideal processing temperature 5°C until 30°C.

Shake before use.

Apply Food Grade Grease in a thin layer.



**SPECIFICATIONS :**

<b>Content:</b>	500 ml
<b>Base:</b>	Mineral Oil and Fat EP
<b>VOS-content:</b>	Circa 71% w/w
<b>Colour:</b>	Beige
<b>Odour:</b>	Characteristic
<b>Appearance:</b>	Fat
<b>Density at 20°C:</b>	0,76 gr/ml
<b>Spray proceeds:</b>	1,5 gr/sec.
<b>Vapour pressure at 20°C:</b>	3 until 4 bar
<b>4 Ball EP-test (ASTM D 2596):</b>	3136 N
<b>4 Ball Wear-test (ASTM D 2266):</b>	< 0,4 mm
<b>Temperature resistant:</b>	-30°C until +160°C
<b>pH-value:</b>	Neutral