

# ANTI SEIZE SPRAY

## LUBRICATION AND MAINTENANCE

- **High thermal stability**
- **Resistant to chemicals and weathering**
- **Excellent corrosion prevention**
- **Excellent adhesion**

### PRODUCT DESCRIPTION :

High quality spray with a high copper content in order to avoid wear and jamming of screw connections which are exposed to very high temperatures. Anti seize spray has a very high thermal stability, is resistant to chemicals and weathering, and provides excellent corrosion protection. Anti seize spray is characterized by an excellent adhesion, prevents wear and malfunction, and therefore facilitates the later removal. It also has a directed jet spray.

### APPLICATIONS :

- Brake parts
- Exhaustion parts
- Screwed connections which are exposed to very high temperatures
- Battery poles
- Screw thread of spark plugs

### INSTRUCTIONS :

Before use, carefully read and follow the directions on the packaging. Bring the aerosol to room temperature. Ideal processing temperature 5 to 30 ° C. Before use, shake the aerosol.

The specific lubricating property of copper paste is achieved after evaporation of the solvent (approx. 1 minute).



**SPECIFICATIONS:**

Contents:	400 ml
Base:	EP Grease with fine copper particles
VOC-content:	Approximately 69% w / w
Solids:	Approximately 31% w / w
Colour:	Copper
Odour:	Characteristic
Appearance:	Pasty
Density at 20 ° C:	0.767 g / ml
Yield:	1.26 g / sec.
Vapour pressure at 20 ° C:	3 to 4 bar
Temperature range:	-40 ° C to + 1100 ° C