

# EASY FLUID

SOLVENTS AND DEGREASERS

- Accelerates skin formation
- Free of acids and solvents
- Pleasant odour

## PRODUCT DESCRIPTION :

Easy Fluid is a neutral universal levelling fluid for sealants in joints.

Easy Fluid is for more than 90 % biodegradable. Easy Fluid is suitable for a flawless finish of all joints in most kinds of sealant applications which harden under the influence of humidity: acrylic, silicone, polyurethane and Ms-polymer sealants.

## APPLICATIONS :

Applications on natural stone: after curing, rinse thoroughly with pure water. For sensitive surfaces: if necessary test on a non-visible place. If the sealant has to be painted over, varnished or refinished: let the glue harden, wipe with a damp cloth and wipe dry.

## USER MANUAL :

After the sealant is applied in the joint surface and the adjacent materials have to be humidified with the Easy Fluid with a brush or a spray bottle.

After this the joint has to be finished with a spatula, Joint wood or a PVC pipe. After the joints is smoothed, it still can be smoothed with a finger wetted with diluted Easy Fluid. After use of Easy Fluid is advised to clean the surfaces or to rinse it with water in order to prevent rutting. Remnants of Easy Fluid may have a negative influence on the flow behaviour and the adhesion of paint.



**SPECIFICATIONS:**

<b>Processing temperature °C:</b>	+5 / +40
<b>Odour:</b>	Week
<b>Density g /ml:</b>	1,03
<b>pH 1%:</b>	7,0 - 7,5
<b>pH 10%:</b>	7,5 - 8,0
<b>pH undiluted:</b>	8,0 - 8,5
<b>Viscosity mPas:</b>	about 5000
<b>Durability between +5C and +25C:</b>	24 Months